


SIMATIC WINCC RUNTIME CLIENT UPGRADE FROM V6.2 TO V7.0 SP3,
FOR WINCC RT CLIENTS (RT128),
INCL. DRIVER, USER ARCHIVE,
CONNECTIVITY PACK, CONNECTIVITY STATION



General information	
Multi-user system	
Multi-user capability	Yes
Number of servers, max.	12
Number of clients for server without operator console, max.	32
Web clients	Yes
Operator control and monitoring	
Object block library	Yes ; Integrated
With alarm logging system (incl. buffer and acknowledgment)	Yes ; Integrated
Report system/log system	Yes
SQL database	Yes ; Integrated
Process diagnostics	No
Sector-specific and technological expansions	No
Recipes	
User archive/recipe management	No
Interfaces	
Programming interfaces	Yes
OPC-DA interface, Server	Yes

OPC-DA interface, Client	Yes
Hardware requirements	
Processor clock frequency, min.	1 GHz
Main memory, min.	1000 Mbyte
Configuration	
Max. number of multiusers configuration	32
Online configuration	Yes
Script languages (Runtime)	
Number of Visual Basic Scripts	Yes
other	Yes
Know-how protection	
Password protection	Yes
Languages	
Configuration languages	
Number of configuration languages	70
Status	Jul 14, 2014