

SAISC-D-RR-8.3-C5**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

The crimp connection is characterised by high functional reliability. With this connection technology, the conductor is crimped to the contact and then engaged in the contact carrier. The connection between the conductor and crimp is vibration-resistant and boasts long-term stability.

General ordering data

| | |
|------------|---|
| Version | Plugs prefabricated to customer spec., M12, pin, straight |
| Order No. | 1380580000 |
| Type | SAISC-D-RR-8.3-C5 |
| GTIN (EAN) | 4050118182613 |
| Qty. | 1 pc(s). |

Creation date March 23, 2021 8:02:23 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

SAISC-D-RR-8.3-C5

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 25 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical data customisable plug-in connectors

| | | | |
|--------------------------------|-----------------------------------|--------------------------------|--|
| Cable diameter | 6.5 mm, 6.6 mm, 7.3 mm, 8.3 mm | Cable diameter, max. | 8.3 mm |
| Cable diameter, min. | 8.3 mm | Category | Cat.5 (ISO/IEC 11801) / Cat.5e (TIA T568-B) |
| Coding | D | Conductor cross-section, max. | 0.5 mm ² |
| Conductor cross-section, min. | 0.34 mm ² | Connection cross-section, max. | 0.5 mm ² |
| Connection cross-section, min. | 0.34 mm ² | Contact surface | Gold-plated |
| Housing main material | CuZn | Number of poles | 4 |
| Plugging cycles | ≥ 200 | Pollution severity | 3 |
| Protection degree | IP67 | Rated current | 4 A |
| Rated voltage | 50 V | Rated voltage (text) | 50 V |
| Shield connection | Yes | Temperature range of housing | -40 ... +85 °C |
| Type of connection | Crimp connection | | |

Standards

| | | | |
|--------------------|-----------------|----------------------------------|-------------------------------------|
| Connector standard | IEC 61076-2-101 | Fire safety for railway vehicles | According to EN 45545, HL1 - HL3 |
|--------------------|-----------------|----------------------------------|-------------------------------------|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC002635 | ETIM 7.0 | EC002635 |
| ECLASS 9.0 | 27-44-01-02 | ECLASS 9.1 | 27-44-01-03 |
| ECLASS 10.0 | 27-44-01-02 | ECLASS 11.0 | 27-44-01-02 |

Approvals

Approvals



ROHS Conform

Downloads

Approval/Certificate/Document of Conformity [PROFINET Manufacturer's Declaration](#)User Documentation [Manual](#)

Data sheet

SAISC-D-RR-8.3-C5

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Pole scheme

