



SIMATIC MOBILE PANEL 277 IWLAN V2 (USA), WITH HANDWHEEL, KEY SWITCH AND TWO ILLUMINATED PUSHBUTTON, CONFIGURABLE W. WINCC FLEXIBLE STANDARD VERSION 2008 AND HIGHER OR TIA PORTAL V11 SP2 AND HIGHER INCL. 1 MAIN BATTERY POWER SUPPLY TO BE ORDERED SEPARATELY: 6AV6671-5CE00-0AX1 CHARGING ST. 6AV6671-5CN00-0AX2 EXTERNAL POWER SUPPLY UNIT (EU/US/UK/JP)

Figure similar

General information	
Customer-specific configuration	Yes
Display	
Design of display	TFT
Screen diagonal	7.5 in
Number of colors	65 536
Color type	Colors
Resolution (pixels)	
• Resolution (WxH in pixel)	640 x 480
• Horizontal image resolution	640 Pixel
• Vertical image resolution	480 Pixel
Backlighting	
• MTBF backlighting (at 25 °C)	50 000 h
Control elements	
Control elements	Keys and Touch
Keyboard fonts	

<ul style="list-style-type: none"> • Membrane keyboard <ul style="list-style-type: none"> — user-definable label membrane keys 	Yes
<ul style="list-style-type: none"> • Function keys <ul style="list-style-type: none"> — Number of function keys — Number of function keys with LEDs 	18 18
<ul style="list-style-type: none"> • Keys with LED 	Yes
<ul style="list-style-type: none"> • Numeric/alphabetical input 	Yes / Yes
<ul style="list-style-type: none"> • Multi-key operation <ul style="list-style-type: none"> — Number of multi-key operations 	Yes 2
Touch operation	
<ul style="list-style-type: none"> • Design as touch screen 	Yes; analog, resistive
Connection type	
<ul style="list-style-type: none"> • Connection for mouse/keyboard/barcode reader 	USB / USB / USB
Special operator controls	
<ul style="list-style-type: none"> • Stop button 	No
<ul style="list-style-type: none"> • Acknowledgement button 	No
<ul style="list-style-type: none"> • Key-operated switch 	Yes
<ul style="list-style-type: none"> • Illuminated pushbutton 	Yes
<ul style="list-style-type: none"> • Handwheel 	Yes
Supply voltage	
Type of supply voltage	DC
Processor	
Processor type	ARM, 520 MHz
Memory	
Type of memory	Flash / RAM
Memory available for user data	6 Mbyte
Main memory <ul style="list-style-type: none"> • Capacity of main memory, max. 	128 Mbyte
Type of output	
Status LEDs	Yes
Power LED	Yes
Time of day	
Clock	
<ul style="list-style-type: none"> • Type 	Hardware clock, battery backup, synchronizable
<ul style="list-style-type: none"> • Hardware clock (real-time) 	Yes
<ul style="list-style-type: none"> • retentive 	Yes
<ul style="list-style-type: none"> • synchronizable 	Yes
Interfaces	
Interfaces/bus type	1 x Ethernet (RJ45)

Number of RS 485 interfaces	0
Number of USB interfaces	1
USB port	1 x USB
Multimedia Card slot	1 MMC/SD card slot
Industrial Ethernet	
• Industrial Ethernet interface	1 x Ethernet (RJ45)

Protocols

PROFINET	Yes
Supports protocol for PROFINET IO	Yes
PROFIsafe	No
PROFIBUS	No

Protocols (Ethernet)

• TCP/IP	Yes
----------	-----

Further protocols

• MODBUS	Yes; Modicon (MODBUS TCP/IP)
• other bus systems	Yes; Allen-Bradley E/IP C.Logix

EMC

Emission of radio interference acc. to EN 55 011

• Limit class A, for use in industrial areas	Yes; The product is designed for use in industrial environments. When used in residential areas, the emission of radio interference according to limit class B of EN 55011 must be ensured. For further information refer to the user documentation
--	---

Degree and class of protection

Enclosure according to EN 60529	IP65
---------------------------------	------

Standards, approvals, certificates

Certifications	CE, cULus, C-TICK
CE mark	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes

Ambient conditions

Free fall

• Fall height, max.	1.2 m
---------------------	-------

Ambient temperature during operation

• min.	0 °C
• max.	40 °C

Ambient temperature during storage/transportation

• min.	-20 °C
• max.	60 °C

Relative humidity

• Operation, max.	80 %
-------------------	------

Operating systems

Operating system	Windows CE
Configuration	
Message indicator	Yes
Alarm logging system (incl. buffer and acknowledgment)	Yes
Process value display (output)	Yes
Process value default (input) possible	Yes
Recipe management	Yes
Configuration software	
<ul style="list-style-type: none"> • WinCC flexible Compact • WinCC flexible Standard • WinCC flexible Advanced • WinCC Basic (TIA Portal) • WinCC Comfort (TIA Portal) • WinCC Advanced (TIA Portal) • WinCC Professional (TIA Portal) • Configuration tool • 2. Configuration kit <ul style="list-style-type: none"> — Version — Configuration tool — Type 	<ul style="list-style-type: none"> No Yes No No Yes; V11 SP2 or higher Yes; V11 SP2 or higher Yes; V11 SP2 or higher WinCC flexible Standard Version 2008 SP2 and higher (to be ordered separately) WinCC flexible Standard Version 2008 SP2 WinCC flexible Standard
Languages	
Online languages	
<ul style="list-style-type: none"> • Number of online/runtime languages 	16
Project languages	
<ul style="list-style-type: none"> • Languages per project 	32
Functionality under WinCC (TIA Portal)	
Libraries	Yes
Applications/options	Internet Explorer, Sm@rtService, Sm@rtAccess
Number of Visual Basic Scripts	Yes
Task planner	Yes
Help system	Yes
<ul style="list-style-type: none"> • Number of characters per info text 	70
Message system	
<ul style="list-style-type: none"> • Number of alarm classes • Number of messages • Bit messages <ul style="list-style-type: none"> — Number of bit messages • Analog messages <ul style="list-style-type: none"> — Number of analog messages 	<ul style="list-style-type: none"> 32 4 000 Yes 4 000 Yes 4 000

• System messages HMI	Yes
• System messages PLC	Yes
• Lines	1
• Number of characters per message	80
• Number of process values per message	8
• Acknowledgment groups	
— Number of acknowledgement groups	99
• Message indicator	Yes
• First/last value	Yes
Recipe management	
• Number of recipes	300
• Data records per recipe	500
• Entries per data record	1 000
• Recipe memory	64 KB integrated Flash, expandable
Variables	
• Number of variables per device	2 048
• Number of variables per screen	200
• Number of variables	1 000
• Initial values	2 048
• Type Date & Time	2 048
• Limit values	Yes
• Multiplexing	Yes
• Structures	Yes
Images	
• Number of configurable images	500
• Permanent window/default	Yes
• Start screen configurable	Yes
• Image selection by PLC	Yes
• Image number in the PLC	Yes
Image objects	
• Text objects	10,000 text elements
• Number of I/O fields per image	200
• Number of date/time fields	200
• Return	Yes
• Graphics object	Bit maps, icons, vector graphics
— Icons	1 000
Complex image objects	
• Status/control	Yes; With SIMATIC S7
• dynamic objects	Diagrams, bar graphs, sliders, analog display, invisible buttons
— Number of objects per project	1 000
— Number of curve diagrams per image	10

• Methods	Trend / profile
• Bar graphs	
— Number of bars per chart	10
• Sliders	
— Number of slides per image	10
• Pointer instruments	
— Number of analog indicators per image	10
• Limit value lines	Yes
• Number of alphanumeric fields	300
— alphanumeric fields per image	200
• Number of numerical fields	2 048
— numerical fields per image	200
• Number of password fields	2 048
• Number of visible switches per project	200
— visible switches per image	200
— hidden switches per image	200
• Number of status switches per project	200
— Number of status switches per image	200
• Number of selector switches per project	200
— Selector switches per image	200
• Number of decade switches per project	200
— Decade switches per image	200
• Number of signal lamps per project	200
— Signal lamps per image	200
Attributes for dynamic objects	
• Color change	Yes
• X/Y movement	Yes
• Hide	Yes
Lists	
• Number of text lists per project	500
• Number of text lists per image	200
• Number of entries per text list	256
• Number of graphics lists per project	400
• Number of graphic lists per image	200
• Number of entries per graphics list	256
Archiving	
• Number of archives per device	20
• Number of measuring points per project	20
• Number of entries per archive	10 000
• Message archive	Yes
• Process value archive	Yes

• Archiving methods	
— Sequential archive	Yes
— Short-term archive	Yes
• Memory location	MultiMediaCard
• Data storage format	
— CSV	Yes
• Online evaluation	
— using trend curves	Yes
Filters	
• cyclic	Yes
• Tolerance	Yes
• Change	Yes
Security	
• Number of user groups	50
• Number of user rights	32
• Password export/import	Yes
Logging through printer	
• Recording/Printing	Alarms, report (shift report), PROFINET
Transfer (upload/download)	
• Transfer of configuration	USB, Ethernet, automatic transfer recognition
Process coupling	
• Connection to controller	S7-200, S7- 300/400 see section on "System interfaces"
• S7-1200	Yes
• S7-1500	Yes
• S7-200	Yes
— Ethernet	Yes
• S7-300/400	Yes
— PROFINET	Yes
• LOGO!	Yes
• SIMOTION	Yes
• Allen Bradley (EtherNet/IP)	Yes
• Mitsubishi (MC TCP/IP)	Yes; WinCC V11 SP2 or higher
• Modicon (Modbus TCP/IP)	Yes
Functions	
• TAB sequence	Yes
• Calculating functions	Yes
• Animate	Yes
Service tools/configuration aids	
• Clean screen	Yes
• Touch calibration	Yes
• Backup/Restore manually	Yes

- Simulation Yes
- Device switchover Yes
- Delta transfer Yes

Peripherals/Options

Peripherals	Barcode reader
• SIMATIC HMI MM memory card: Multi Media Card	Yes
• SIMATIC HMI SD memory card: Secure Digital memory card	Yes
• USB memory	Yes
Additional software components loadable	Yes

Mechanics/material

Type of housing (front)	plastic
-------------------------	---------

Dimensions

Enclosure diameter	290 mm
Depth of housing	103 mm

Weights

Weight (without packaging)	2.2 kg
----------------------------	--------

Other

free hotline	Yes
Warranty period	1 y
last modified:	08/25/2016