



TOUCH PEN,  
THIN FOR RESISTIVE TOUCHSCREEN HOLDING CORD  
FOR MOBILE PANEL 277 10" AND OTHER RESISTIVE  
TOUCH DISPLAYS AMOUNT AND CONTENT: SEE  
TECHNICAL DATA

Installation type/mounting	
Wall mounting/direct mounting possible	Yes ; using 40 cm retaining cord
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Operating temperature	
Operating temperature range, min.	0 °C
Operating temperature range, max.	55 °C
Storage/transport temperature	
min.	-20 °C
max.	70 °C
Relative humidity	
Operation, max.	90 %
Mechanics/material	
Plastic	Yes
Dimensions	
Height	125 mm ; Length
Thickness	8 mm ; Diameter

Scope of supply	
Delivery unit in items	5 ; Incl. retaining cord for Mobile Panel 277 10"
Other	
Note:	for resistive touch screens
Usable in the following products	
Product 1	<a href="#">6AV6642-0AA11-0AX0</a>
Product 2	<a href="#">6AV6642-0AA11-0AX1</a>
Product 3	<a href="#">6AV6642-0BD01-3AX0</a>
Product 4	<a href="#">6AV6642-0BA01-1AX1</a>
Product 5	<a href="#">6AV6642-0BC01-1AX1</a>
Product 6	<a href="#">6AV6642-0DC01-1AX0</a>
Product 7	<a href="#">6AV6642-0DA01-1AX0</a>
Product 8	<a href="#">6AV6545-0DA10-0AX0</a>
Product 9	<a href="#">6AV6545-0DB10-0AX0</a>
Product 10	<a href="#">6AV6545-0AA15-2AX0</a>
Product 11	<a href="#">6AV3637-1PL00-0AX0</a>
Product 12	<a href="#">6AV6642-0EA01-3AX0</a>
Product 13	<a href="#">6AV6644-0CB01-2AX0</a>
Product 14	<a href="#">6AV6643-8AD10-0AA0</a>
Product 15	<a href="#">6AV6640-0CA01-0AX0</a>
Product 16	<a href="#">6AV6545-0AH10-0AX0</a>
Product 17	<a href="#">6AV6545-0AH10-0AX1</a>
Product 18	<a href="#">6AV6640-0CA01-0AX0</a>
Product 19	<a href="#">6AV6545-0CC10-0AX0</a>
Product 20	6AV2123-2*
Status	Aug 7, 2014