

SIEMENS

Product data sheet

6ES7131-4BB01-0AB0


SIMATIC DP,
 5 ELECTRON. MODULES FOR ET 200S,
 2 DI HIGH FEATURE 24V DC,
 15 MM WIDTH WITH PARAM. F. INPUT DELAY
 DIAGNOSIS F. ENCODER SHORT- CIRCUIT W. LED
 SF (GROUP FAULT) 5 PIECES PER PACKAGING
 UNIT

Supply voltage	
24 V DC	Yes ; From power module
permissible range, lower limit (DC)	20.4 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
from backplane bus 3.3 V DC, max.	10 mA
from supply voltage L+, max.	Dependent on encoder
Encoder supply	
Output voltage	min. L+ (-0.5 V), under load
Output current, rated value	500 mA
Output current, permissible range	0 to 500 mA
Output current	
Short-circuit protection	Yes ; Electronic
Power losses	

Power loss, typ.	0.4 W
Address area	
Address space per module	
with packing	2 bit
without packing	1 byte
Digital inputs	
Number/binary inputs	2
Input characteristic curve acc. to IEC 61131, Type 1	Yes
Input voltage	
Type of input voltage	DC
Rated value, DC	24 V
for signal "0"	-30 to +5 V
for signal "1"	11 to 30 V
Input current	
for signal "1", typ.	8 mA
Input delay (for rated value of input voltage)	
for standard inputs	
Parameterizable	Yes ; 0.1 / 0.5 / 3 / 15 ms
at "0" to "1", min.	0.05 / 0.4 / 2.7 / 14.85
at "0" to "1", max.	0,15 / 0,6 / 3,3 / 15,15
at "1" to "0", min.	0.05 / 0.4 / 2.7 / 14.85
at "1" to "0", max.	0,15 / 0,6 / 3,3 / 15,15
Cable length	
Cable length, shielded, max.	1000 m
Cable length unshielded, max.	600 m
Encoder	
Connectable encoders	
2-wire sensor	Yes
Permissible quiescent current (2-wire sensor), max.	1.5 mA
Interrupts/diagnostics/status information	
Diagnostic messages	
Diagnostic functions	Yes

Short circuit	Yes ; Short-circuit of outputs to ground; module by module
Diagnostics indication LED	
Group error SF (red)	Yes
Status indicator digital input (green)	Yes ; per channel
Parameter	
Diagnosis: short circuit	Disable / enable
Galvanic isolation	
Galvanic isolation digital inputs	
between the channels	No
between the channels and the backplane bus	Yes
Permissible potential difference	
between different circuits	75 VDC / 60 VAC
Isolation	
Isolation checked with	500 V DC
Dimensions	
Width	15 mm
Height	81 mm
Depth	52 mm
Weight	
Weight, approx.	35 g
Status	Jul 17, 2012