



SIMATIC ET 200SP,  
DIGITAL OUTPUT MODULE,  
DQ 4X24VDC/2A STANDARD,  
FITS TO BU-TYPE A0, COLOR CODE CC02,  
MODULE DIAGNOSIS

General information	
usable BaseUnits	BU type A0
Color code for module-specific color identification plate	CC02
Product function	
I&M data	Yes
Engineering with	
STEP 7 TIA Portal configurable/integrated as of version	V11 SP2 / V13
STEP 7 configurable/integrated as of version	V5.5 SP3 / -
PROFIBUS as of GSD version/GSD revision	GSD as of Revision 5
PROFINET as of GSD version/GSD revision	V2.3 / -
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption, max.	60 mA ; without load
Power loss	
Power loss, typ.	1 W

Address area	
Address space per module	
Address space per module, max.	1 byte
Digital outputs	
Number of digital outputs	4
Short-circuit protection	Yes
Response threshold, typ.	2.8 to 5.2 A
Limitation of inductive shutdown voltage to	Typ. L+ (-50 V)
Controlling a digital input	Yes
Switching capacity of the outputs	
with resistive load, max.	2 A
on lamp load, max.	10 W
Load resistance range	
lower limit	12 Ω
upper limit	3400 Ω
Output current	
for signal "1" rated value	2 A
for signal "0" residual current, max.	0.1 mA
Output delay with resistive load	
"0" to "1", max.	50 µs
"1" to "0", max.	100 µs
"0" to "1", typ.	50 µs
"1" to "0", typ.	100 µs
Parallel switching of 2 outputs	
for uprating	No
for redundant control of a load	Yes
Switching frequency	
with resistive load, max.	100 Hz
with inductive load, max.	2 Hz
on lamp load, max.	10 Hz
Total current of the outputs	
Max. current per module	8 A
Total current of the outputs (per module)	
horizontal installation	
up to 40 °C, max.	8 A
up to 50 °C, max.	6 A
up to 60 °C, max.	4 A
vertical installation	

up to 40 °C, max.	6 A
up to 50 °C, max.	4 A
up to 60 °C, max.	4 A
<b>Cable length</b>	
Cable length, shielded, max.	1000 m
Cable length unshielded, max.	600 m
<b>Interrupts/diagnostics/status information</b>	
Substitute values connectable	Yes
<b>Alarms</b>	
Diagnostic alarm	Yes
<b>Diagnostic messages</b>	
Monitoring the supply voltage	Yes
Wire-break	Yes
Short-circuit	Yes
<b>Diagnostics indication LED</b>	
Monitoring the supply voltage (PWR-LED)	Yes ; green PWR LED
Channel status display	Yes ; Green LED
for module diagnostics	Yes ; green/red DIAG LED
<b>Galvanic isolation</b>	
<b>Galvanic isolation channels</b>	
between the channels	No
between the channels and the backplane bus	Yes
<b>Permissible potential difference</b>	
between different circuits	75 V DC/60 V AC (base isolation)
<b>Isolation</b>	
Isolation tested with	707 V DC (type test)
<b>Ambient conditions</b>	
<b>Operating temperature</b>	
horizontal installation, min.	0 °C
horizontal installation, max.	60 °C
vertical installation, min.	0 °C
vertical installation, max.	50 °C
<b>Dimensions</b>	
Width	15 mm
<b>Weights</b>	
Weight, approx.	30 g
Status	Aug 4, 2014