

permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Input current	
Current consumption (rated value)	29 mA
Power loss	
Power loss, typ.	0.7 W
Address area	
Occupied address area	
• Inputs	8 byte
Interfaces	
1. Interface	
Interface types	
— RS 232	Yes
— RS 422	Yes
— RS 485	Yes
Interface types	
RS 232	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	15 m
• RS 232 auxiliary signals	RTS, CTS, DTR, DSR, RI, DCD
RS 485	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	1 200 m
RS 422	
• Transmission rate, max.	115.2 kbit/s
• Cable length, max.	1 200 m
• 4-wire full duplex connection	Yes
• 4-wire multipoint connection	Yes
Protocols	
Integrated protocols	
Freeport	
— Telegram length, max.	2 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit
— Parity	None, even, odd, always 1, always 0, any
3964 (R)	
— Telegram length, max.	2 kbyte
— Bits per character	7 or 8
— Number of stop bits	1 or 2 bit

— Parity	None, even, odd, always 1, always 0, any
Modbus RTU master	
— Address area	1 to 247, extended 1 to 65535
— Number of slaves, max.	32
MODBUS RTU slave	
— Address area	1 to 247, extended 1 to 65535
Telegram buffer	
• Buffer memory for telegrams	4 kbyte
• Number of telegrams which can be buffered	255

Interrupts/diagnostics/status information

Alarms	
• Diagnostic alarm	Yes
• Hardware interrupt	No
Diagnostic messages	
• Diagnostics	Yes
• Wire-break	Yes
Diagnostics indication LED	
• Monitoring of the supply voltage (PWR-LED)	Yes; green PWR LED
• for module diagnostics	Yes; green/red DIAG LED
• Receive RxD	Yes; Green LED
• Transmit TxD	Yes; Green LED

Potential separation

between backplane bus and interface	Yes
-------------------------------------	-----

Permissible potential difference

between different circuits	75 V DC/60 V AC (base isolation)
----------------------------	----------------------------------

Isolation

Isolation tested with	707 V DC (type test)
-----------------------	----------------------

Decentralized operation

to SIMATIC S7-300	Yes
to SIMATIC S7-400	Yes
to SIMATIC S7-1200	Yes
to SIMATIC S7-1500	Yes
to standard PROFINET controller	Yes

Dimensions

Width	15 mm
-------	-------

Weights

Weight, approx.	30 g
-----------------	------

last modified: 12.09.2015