



SIMATIC DP,
POWER MODULES OUTPUT FOR ELECTRONIC
MODULES ET 200PRO PM-O,
DC 2X24V INCLUSIVE BUS MODULE CONNECTING
MODULE PM-O 6ES7194-4BH00-0AA0 MUST BE
ORDERED SEPERATELY

Supply voltage	
Load voltage 2L+	
Short-circuit protection	Yes
Reverse polarity protection	Yes ; against destruction
Current carrying capacity	
Current carrying capacity, max.	Output current 2 A for 1L+ and 6 A for 2L+
Interrupts/diagnostics/status information	
Diagnostic messages	
Diagnostic functions	Yes
Diagnostic information readable	Yes
Fuse blown	No ; Indirect diagnostics (short-circuit to M for 1L+), since electronic fuse
missing load voltage	No
Diagnostics indication LED	
Rated load voltage PWR (green)	No
Group error SF (red)	Yes
Load voltage monitoring 24 V DC (green)	No ; Signalled in IM or in PM
Parameter	
Remark	Diagnosis short circuit implemented after M for 1L+

Galvanic isolation	
primary/secondary	No
Isolation	
Isolation tested with	500 V DC
Degree and class of protection	
IP65	Yes
IP66	Yes
IP67	Yes
Dimensions	
Width	45 mm
Height	130 mm
Depth	35 mm
Weights	
Weight, approx.	150 g
Status	Jul 28, 2014