6ES7221-3AD30-0XB0 Page 1

SIEMENS

Product data sheet

6ES7221-3AD30-0XB0



SIMATIC S7-1200, DIGITAL INPUT SB 1221, 4DI, 5VDC 200KHZ

Input current	
from backplane bus 5 V DC, typ.	50 mA
Output voltage	
Power supply to the transmitters	
Supply current, max.	4 mA; per channel
Power losses	
Power loss, typ.	1 W
Digital inputs	
Number/binary inputs	4 ; Current-sourcing
In groups of	1
Input characteristic curve acc. to IEC 61131, Type 1	Yes
Number of simultaneously controllable inputs	
all mounting positions	
up to 40 °C, max.	4
Input voltage	

6ES7221-3AD30-0XB0 Page 2

Rated value, DC	5 V
for signal "0"	0 to 1 V
for signal "1"	2 to 6 V
Input current	
for signal "0", max. (permissible quiescent current)	3 mA
for signal "1", min.	6 mA
Input delay (for rated value of input voltage)	
for standard inputs	
Parameterizable	Yes; 0.2, 0.4, 0.8, 1.6, 3.2, 6.4, and 12.8 ms, selectable in groups of four
at "0" to "1", max.	2 μs
for interrupt inputs	
Parameterizable	Yes
for counter/technological functions	
Parameterizable	Yes
Cable length	
Cable length, shielded, max.	50 m ; Shielded, twisted wire pair
Interrupts/diagnostics/status information	
Alarms	
Alarms	Yes
Diagnostic messages	
Diagnostic functions	Yes
Diagnostics indication LED	
for status of the inputs	Yes
Degree and class of protection	
IP20	Yes
Standards, approvals, certificates	
Marine approval according to Germanischer Lloyd	Yes
Climatic and mechanical conditions for storage and trans	sport
Climatic conditions for storage and transport	
Free fall	
Drop height, max. (in packaging)	0.3 m; five times, in dispatch package
Temperature	
Permissible temperature range	-40 °C to +70 °C

6ES7221-3AD30-0XB0 Page 3

Air pressure acc. to IEC 60068-2-13		
Permissible air pressure	1080 to 660 hPa	
Mechanical and climatic conditions during operation		
Climatic conditions in operation		
Temperature		
Permissible temperature range	0 °C to 55 °C horizontal installation 0 °C to 45 °C vertical installation	
Mechanics/material		
Type of housing (front)		
Plastic	Yes	
Dimensions		
Width	38 mm	
Height	62 mm	
Depth	21 mm	
Weight		
Weight, approx.	40 g	
Status	Jul 17, 2012	