

SIEMENS

Product data sheet

6ES7231-5PA30-0XB0

SIMATIC S7-1200, RTD INPUT,
SB 1231 RTD, 1 AI RTD, 1 CHANNEL,
PT 100 AND PT1000

Supply voltage	
24 V DC	Yes
Input current	
Current consumption, typ.	5 mA
from backplane bus 5 V DC, typ.	20 mA
Power losses	
Power loss, typ.	0.5 W
Analog inputs	
Number of analog inputs	1 ; Resistance thermometer
permissible input frequency for current input (destruction limit), max.	± 35 V
Technical unit for temperature measurement adjustable	Degrees Celsius/degrees Fahrenheit
Input ranges	
Resistance thermometer	Yes ; Platinum (Pt)
Resistance	Yes ; 150 Ω, 300 Ω, 600 Ω
Input ranges (rated values), voltages	
Input resistance (-80 mV to +80 mV)	>= 10 MOhm
Input ranges (rated values), resistance thermometers	
Pt 100	Yes
Input resistance (Pt 100)	100 Ω
Pt 1000	Yes
Input resistance (Pt 1000)	1000 Ω
Pt 200	Yes
Input resistance (Pt 200)	200 Ω
Pt 500	Yes

Input resistance (Pt 500)	500 Ω
Input ranges (rated values), resistors	
0 to 150 ohms	Yes
0 to 300 ohms	Yes
0 to 600 ohms	Yes
Thermocouple (TC)	
Temperature compensation	
Parameterizable	No
Analog value creation	
Measurement principle	integrating
Integrations and conversion time/ resolution per channel	
Resolution with overrange (bit including sign), max.	15 bit ; + sign
Integration time, parameterizable	No
Interference voltage suppression for interference frequency f1 in Hz	85 dB at 10 / 50 / 60 / 400 Hz
Errors/accuracies	
Temperature error (relative to input area)	25 °C \pm 0.1 % to 55 °C \pm 0.2 % total measurement range
Interference voltage suppression for $f = n \times (f1 \pm 1\%)$, f1 = interference frequency	
Common mode interference, min.	120 dB
Interrupts/diagnostics/status information	
Alarms	
Alarms	Yes
Diagnostic alarm	Yes
Diagnostic messages	
Diagnostic functions	Yes ; Can be read out
Wire break	Yes
Diagnostics indication LED	
for status of the inputs	Yes
for maintenance	Yes
Degree and class of protection	
IP20	Yes
Standards, approvals, certificates	

CE mark	Yes
C-TICK	Yes
FM approval	Yes
Climatic and mechanical conditions for storage and transport	
Climatic conditions for storage and transport	
Free fall	
Drop height, max. (in packaging)	0.3 m ; five times, in dispatch package
Temperature	
Permissible temperature range	-40 °C to +70 °C
Air pressure acc. to IEC 60068-2-13	
Permissible air pressure	1080 to 660 hPa
Mechanical and climatic conditions during operation	
Climatic conditions in operation	
Temperature	
Permissible temperature range	0 °C to 55 °C horizontal installation 0 °C to 45 °C vertical installation
Air pressure acc. to IEC 60068-2-13	
Permissible air pressure	1080 to 795 hPa
Pollutant concentrations	
SO2 at RH < 60% without condensation	SO2: < 0.5 ppm; H2S: < 0.1 ppm; RH < 60% condensation-free
Connection method	
required front connector	Yes
Mechanics/material	
Type of housing (front)	
Plastic	Yes
Dimensions	
Width	38 mm
Height	62 mm
Depth	21 mm
Weight	
Weight, approx.	35 g
Status	Jul 17, 2012