



SIMATIC DP,
BUS CONNECTOR FOR PROFIBUS UP TO 12 MBIT/S
WITH TILTED CABLE OUTLET,
15,8 X 54 X 39,5 MM (WXHxD),
TERMINAT. RESIST. WITH ISOLAT. FUNCTION,
WITH PG SOCKET

Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables
- for network components and terminal equipment

2

1

Design of the electrical connection / FastConnect

No

Mechanical data

material / of the housing

plastic

Design, dimensions and weight

Width

15.8 mm

Height

54 mm

Depth

39.5 mm

Net weight

67 g

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

0 ... 60 °C

-40 ... +70 °C

-40 ... +70 °C

Relative humidity

- at 25 °C / without condensation / during operating / maximum

95 %

Protection class IP	IP20
Product properties, functions, components / general	
Product feature / [not supplied - silicon-free]	Yes
Composant produit	
• PG connection socket	Yes
• décharge de traction	Yes
Standards, specifications, approvals	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	Yes
letzte Änderung:	Jul 17, 2012