

Product-type designation CP 1623



COMMUNICATION PROCESSOR CP 1623 PCI EXPRESS X1 (3.3V/12V) FOR CONNECTING WITH IND.ETHERNET(10/100/1000MBIT/S) WITH 2-PORT-SWITCH(RJ45) VIA HARDNET-IE S73 AND S7-REDCONNECT SUPPORT FOR OPERATING SYSTEM SEE SIMATIC NET SW ENABLED FOR SIMATIC NET CD V7.0 HF1 OR HIGHER

Transmission rate

Transfer rate / at the interface 1 10 ... 1000 Mbit/s

Interfaces

Number of electrical connections	
• at interface 1 / in accordance with Industrial Ethernet	2
• for power supply	1
Design of electrical connection	
• at interface 1 / in accordance with Industrial Ethernet	RJ45 port

Supply voltage, current consumption, power loss

Type of / supply voltage	DC
Type of power supply / optional external supply	Yes
Supply voltage	
• 1 / from backplane bus	3.3 V
• 2 / from the backplane bus	12 V
• external	24 V
Relative symmetrical tolerance	
• at 3.3 V / with DC	9 %
• at 5 V / with DC	5 %
• at 12 V / with DC	8 %
• at 24 V / with DC	33 %

Consumed current	
• 1 / from backplane bus / with DC / maximum	0.85 A
• 2 / from backplane bus / with DC / maximum	0.4 A
• from external supply voltage	
• at 12 V / with DC / max.	0.55 A
• at 24 V / with DC / maximum	0.3 A
Resistive loss	7.6 W
• in switch mode / maximum	7.2 W
Permitted ambient conditions	
Ambient temperature	
• during operating	5 ... 55 °C
• during storage	-20 ... +60 °C
• during transport	-20 ... +60 °C
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Protection class IP	IP00
Design, dimensions and weight	
Module format	PCI Express x1 (half length)
Width	18 mm
Height	111 mm
Depth	167 mm
Net weight	124 g
Product properties, functions, components / general	
Number of plug-in cards in the same design / can be plugged in / per PC station	4
Number of modules / note	-
Performance data	
Performance data / open communication	
Software / for open communication / by means of SEND/RECEIVE / required	Yes, HARDNET-IE S7 (S7-1613)
Number of possible connections / for open communication / by means of SEND/RECEIVE / maximum	120
Performance data / S7 communication	
Software / for S7 communication / required	Yes, HARDNET-IE S7 (S7-1613)
Number of possible connections	
• for S7/PG communication / maximum	120
• for optimized S7 communication / maximum	40
Performance data / multi-protocol mode	
Number of active connections / with multiprotocol mode	120
Number of configurable connections / per PC station	207
Performance data / PROFINET CBA	

Software / for PROFINET CBA communication / required	Yes, PN CBA OPC server
Number of remote connection partners / with PROFINET CBA	228
Number of connections / with PROFINET CBA / total	10000
Product functions / management, configuration	
Product function / MIB support	Yes
Protocol / is supported	
• SNMP v1	Yes
• SNMP v3	No
• DCP	Yes
Configuration software	
• for PROFINET CBA / required	Yes, SIMATIC iMAP
Identification & maintenance function	
• I&M0 - device-specific information	Yes
• I&M1 – higher level designation/location designation	Yes
Product functions / switch	
Product feature / switch	Yes
Product function	
• switch-managed	No
• for IRT / PROFINET IO switch	No
Product functions / Redundancy	
Software / for redundancy function / required	Yes, HARDNET-IE S7-REDCONNECT for communication with SIMATIC S7 H systems
Product functions / Time	
Product function / SICLOCK support	Yes
Protocol / is supported / NTP	No
Standards, specifications, approvals	
Standard	
• for EMC	2004/108/EC
• for safety / of CSA and UL	CAN/CSA C22.2 & UL 60950-1, UL 1950
• for emitted interference	EN 61000-6-3, EN 61000-6-4
• for interference immunity	EN 61000-6-1, EN 61000-6-2
Verification of suitability	
• CE mark	Yes
• C-Tick	Yes
Security information	

Security information

Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action (e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit <http://www.siemens.com/industrialsecurity>. To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit <http://support.automation.siemens.com>. Version 3.4 – 14.11.2013-Siemens AG, I IA L CG, Nuremberg

letzte Änderung:

Jun 16, 2014