



PB BUS CONNECTOR WITH AXIAL CABLE OUTLET
 F.INDUSTR. PC,
 SIMATIC OP, OLM;
 TRANSMISSION RATE 12 MBIT/S;
 TERMINATING RESISTOR WITH SEPARATING
 FUNCTION,
 METAL HOUSING

Transfer rate

- with PROFIBUS

9.6 kbit/s ... 12 Mbit/s

Interfaces

Number of electrical connections

- for PROFIBUS cables
- for network components and terminal equipment

2

1

Design of the electrical connection / FastConnect

No

Mechanical data

material / of the housing

metal

Design, dimensions and weight

Width

15 mm

Height

57 mm

Depth

39 mm

Net weight

100 g

Permitted ambient conditions

Ambient temperature

- during operating
- during storage
- during transport

0 ... 60 °C

-25 ... +80 °C

-25 ... +80 °C

Relative humidity

- at 25 °C / without condensation / during operating / maximum

75 %

Protection class IP	IP20
Product properties, functions, components / general	
Product feature / [not supplied - silicon-free]	Yes
Composant produit	
• PG connection socket	No
• décharge de traction	Yes
Standards, specifications, approvals	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	No
letzte Änderung:	Jul 17, 2012