

### Product-type designation

### IE SC RJ POF Plug PRO (Push Pull)



IE SC RJ POF PLUG PRO,  
FO PLUG FOR ON-SITE MOUNTING TO POF FO CABLES  
(PACKAGING UNIT 1 DUPLEX- CONNECTOR)

Acceptability for application

Field-assembly connector for push-pull device connection in high degree of protection

Transfer rate

- 1 / for Industrial Ethernet

100 Mbit/s

### Interfaces

Number of optical interfaces / for optical waveguide

1

Design of optical connections / for network components or terminal devices

SC RJ connector (Push Pull device connection)

Design of the electrical connection / FastConnect

No

### Mechanical data

Material / of the enclosure

plastic

### Design, dimensions and weight

Type of cable outlet

180 degree cable outlet

Width

22 mm

Height

30 mm

Depth

62.5 mm

Net weight

63.5 g

### Permitted ambient conditions

Ambient temperature

- during operating

-40 ... +70 °C

• during storage	-40 ... +70 °C
• during transport	-40 ... +70 °C
Protection class IP	IP65/67
Chemical resistance / to water	resistant
<b>Product properties, functions, components / general</b>	
Product feature / silicon-free	Yes
Product component	
• strain relief	Yes
<b>Standards, specifications, approvals</b>	
Verification of suitability	
• RoHS conformity	Yes
• UL-registration	No
<b>letzte Änderung:</b>	Aug 6, 2014