

<b>Product-type designation</b>	<b>RUGGEDCOM RX5000PN LM BLANK</b>
<b>Product description</b>	RX5000 blank line module BLANK MODULE LM
<b>Suitability for installation</b>	RX5000
<b>Permitted ambient conditions</b>	
Ambient temperature	
• during operating	-40 ... +85 °C
• during storage	-40 ... +85 °C
• during transport	-40 ... +85 °C
• Comment	For a period of 16 hours a maximum operating temperature of +85 Cel is possible
Relative humidity / at 25 °C / without condensation / during operating / maximum	95 %
Coating	no
Protection class IP	IP40
<b>Design, dimensions and weight</b>	
Design	Media module
Net weight	1 kg
Mounting type	
• Installation in media module slot	Yes
Mounting type	Screwed
<b>Standards, specifications, approvals</b>	
Standard	
• for EMC	FCC Part 15 (Class A), EN55022 (CISPR22 Class A)
• for safety / of CSA and UL	UL 60950-1, CSA C22.2 No. 60950-7
• for hazardous area / of CSA and UL	Hazardous Locations: Class 1 Division 2
• for emitted interference	EN 61000-6-4 (Class A)
• for interference immunity	EN 61000-6-2
Verification of suitability	EN 61000-6-2, EN 61000-6-10
• CE mark	Yes
• C-Tick	No
• KC approval	No
• E1 approval	No
• Railway application in accordance with EN 50155	Yes
• Railway application in accordance with EN 50124-1	Yes
• IEC 61850-3	Yes

## Further Information / Internet Links

### Internet-Link

- to website: Industry Mall/RUGGEDCOM-Selector <http://ruggedcom-selector.automation.siemens.com>
- to website: Industry Mall <http://www.siemens.com/industrial-controls/mall>
- to website: Selector for cables and connectors <http://www.siemens.com/snst>
- to website: Siemens RUGGEDCOM <http://siemens.com/ruggedcom>
- to website: Industrial communication <http://www.siemens.com/simatic-net>
- to website: Information and Download Center <http://www.siemens.com/automation/net/catalog>
- to website: Image database <http://automation.siemens.com/bilddb>
- to website: CAx Download Manager <http://www.siemens.com/cax>
- to website: Industry Online Support <http://support.automation.siemens.com>

### letzte Änderung / last change:

Aug 6, 2014