

AAM 4 YE FLASH**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image**Building installation wiring**

For building installations, we offer a complete system that revolves around the 10×3 copper rail and comprises perfectly coordinated components: from installation terminal blocks, neutral conductor terminal blocks and distribution terminal blocks to comprehensive accessories such as busbars and busbar holders.

General ordering data

| | |
|------------|--------------------------------------|
| Version | Terminal marker, 10 x 6.1 mm, yellow |
| Order No. | 2635560000 |
| Type | AAM 4 YE FLASH |
| GTIN (EAN) | 4050118674507 |
| Qty. | 40 pc(s). |

AAM 4 YE FLASH

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|----------------|-----------|-----------------|------------|
| Depth | 5.8 mm | Depth (inches) | 0.228 inch |
| Height | 10 mm | Height (inches) | 0.394 inch |
| Net weight | 3.3 g | Width | 6.1 mm |
| Width (inches) | 0.24 inch | | |

Temperatures

Operating temperature range -40...100 °C

Material data

| | | | |
|---------------------------|--------|--------|--------|
| Material | PA 6.6 | Colour | yellow |
| UL 94 flammability rating | V-2 | | |

Rating data IECEx/ATEX

Operating temperature range -40...100 °C

General

Operating temperature range, max. 100 °C Operating temperature range, min. -40 °C

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000761 | ETIM 7.0 | EC000761 |
| ECLASS 9.0 | 27-14-11-37 | ECLASS 9.1 | 27-14-11-37 |
| ECLASS 10.0 | 27-14-11-37 | ECLASS 11.0 | 27-28-11-01 |

Downloads

Brochure/Catalogue [Catalogues in PDF-format](#)