

THROUGH-TYPE TERMINAL SECTIONALIZING FEATURE
SCREW TERMINAL ON BOTH ENDS 6MM,
SZ 2.5



Similar to image

Technical data:

Mounting type		others
Type of longitudinal separation		others
Type of lateral separation		without
Length	mm	41
Color		grey
Height / with lowest-profile installation	mm	29
Number of terminal levels		1
Number of terminal points / per terminal level		2
Design of terminal / terminal levels linked internally		No
Operating voltage / rated value	V	300
Operating current / rated value	A	10
Combustibility class acc. to UL 94		others
Terminal contact spacing	mm	6
Position / of terminal		top
Product component		
• required / connection plate		No
• Test socket		Yes
Design of the electrical connection		

• 1		screw-type terminal
• 2		screw-type terminal
Conductor cross-section that can be connected		
• solid	mm ²	0.25 ... 4
• multibrin	mm ²	0.5 ... 2.5
• finely stranded		
• with wire end processing	mm ²	0.5 ... 1.5
• without wire end processing	mm ²	0.5 ... 2.5

Certificates/approvals:

General Product Approval	Declaration of Conformity	other
 CSA  GOST  UL	 EG-Konf.	other Environmental Confirmations

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WA1501>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/8WA1501/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1501

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014