SIEMENS

Product data sheet   **8WD4408-0AA**

SIGNALLING COLUMN CONNECT. ELEMENT FOR WITH
PIPE MOUNTING COVER LID

General technical details:		
product brand name		SIRIUS
product designation		signaling columns element, connection module
Type of voltage		
• of the operating voltage		AC/DC
Operating frequency		
• 1 / rated value	Hz	50
• 2 / rated value	Hz	60
Operating voltage		
• for DC / rated value	V	230 … 24
• at 50 Hz / at AC / rated value	V	24 … 230
• at 60 Hz / at AC / rated value	V	24 … 230
Item designation		
• according to DIN 40719 extendable after IEC 204-2 / according to IEC 750		E
• according to DIN EN 61346-2		X

Mechanical design:		
Design of the electrical connection		screw-type terminals
Type of mounting		
• pipe mounting		Yes

02/21/2013

• angle mounting			No
• floor mounting			No
Color / of the housing			black
External diameter / of the signal column element		mm	70

Ambient conditions:

Ambient temperature			
• during operating		°C	-20 … +50
Protection class IP			IP65
Depth		mm	40
Height		mm	42
Width		mm	70

Certificates/approvals:

General Product Approval		EMC	Declaration of Conformity	Shipping Approval
GOST	UL	C-TICK	EG-Konf.	DNV

Further information:

Information- and Downloadcenter (Catalogs, Brochures,…)
http://www.siemens.com/industrial-controls/catalogs

Industry Mall (Online ordering system)
http://www.siemens.com/industrial-controls/mall

**Cax online generator:**
http://www.siemens.com/cax

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
http://support.automation.siemens.com/WW/view/en/8WD4408-0AA/all

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)
http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WD4408-0AA

02/21/2013

70

42,5

⌀ ...70

\pi
\pi

last change: Jan 23, 2013