

ISOLATING TERMINAL WITH SCREW CONNECTION,
SECTION: 16 MM² WIDTH: 10 MM,
COLOR: GREEN-YEL.



Similar to image

| Technical data: | | |
|--|----|---------------------|
| Operating current / rated value | A | 101 |
| Mounting type | | DIN rail 35 mm |
| Combustibility class acc. to UL 94 | | others |
| Material / of the insulating body | | Other |
| Design of the electrical connection | | |
| • 1 | | screw-type terminal |
| • 2 | | screw-type terminal |
| Design tested acc. to type of protection / EEx e | | No |
| Product component / required / connection plate | | Yes |
| Number of terminal levels | | 1 |
| Number of terminal points / per terminal level | | 2 |
| Design of terminal / terminal levels linked internally | | No |
| Terminal contact spacing | mm | 12.2 |
| Position / of terminal | | top |
| Height / with lowest-profile installation | mm | 47 |
| Color | | miscellaneous |
| Length | mm | 42.5 |
| Ambient temperature | | |

| | | |
|--|-----------------|-------------|
| • during operating | °C | -25 ... +55 |
| Conductor cross-section that can be connected | | |
| • solid | mm ² | 1.5 ... 16 |
| • multibrin | mm ² | 1.5 ... 16 |
| • finely stranded | | |
| • without wire end processing | mm ² | 1.5 ... 16 |
| • with wire end processing | mm ² | 1.5 ... 16 |

Certificates/approvals:

General Product Approval



Declaration of Conformity



Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH1001-0CK07>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/8WH1001-0CK07/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH1001-0CK07

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Aug 4, 2014