



Similar to image

FUSE TERMINAL WITH ILLUM. DISPLAY (15 - 30V) FOR G FUSE LINKS 5 X 20, 5 X 25 AND 5 X 30 MM WITH 4 MM² SPRING CONNECTION, WIDTH: 6.2 MM, COLOR: BLACK

Technical data:

Mounting type		DIN rail 35 mm
Length	mm	61.5
Color		black
Terminal contact spacing	mm	6.2
Design of fuse holder		pluggable
Design of the fuse link		glass fuse 5x20 mm
Height / with lowest-profile installation	mm	62.5
Type of voltage / for supply of the fault indicator		others
Type of lamp / as fault indicator		LED
Number of terminal levels		1
Combustibility class acc. to UL 94		V0
Insulation material		others
Position / of terminal		top
Product component / required / connection plate		No
Tension d'alimentation / pour affichage de défauts / maximum	V	30
Operating voltage / rated value	V	250
Operating current / rated value	A	6.3
Design of the electrical connection		

• 1		spring-loaded terminal
• 2		spring-loaded terminal
Conductor cross-section that can be connected		
• solid	mm ²	6 ... 6
• multibrin	mm ²	6 ... 6
• finely stranded		
• with wire end processing	mm ²	4 ... 4
• without wire end processing	mm ²	4 ... 4

Certificates/approvals:

General Product Approval



Declaration of Conformity

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH2000-1JG38>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/8WH2000-1JG38/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH2000-1JG38

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Mar 17, 2014