

**H2,5/16T GR BD GSP****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Similar to illustration**

- Linked wire-end ferrules on reel (5,000 pcs.)
- DIN colour code
- other colour code

**General ordering data**

Version	Wire-end ferrule, insulated, 12 mm, 10 mm, grey
Order No.	<a href="#">1476 120000</a>
Type	H2,5/16T GR BD GSP
GTIN (EAN)	4050 118283020
Qty.	3,000 pc(s).
Packaging	Reel

Creation date March 24, 2021 12:51:30 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**H2,5/16T GR BD GSP**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight	0.201 g
------------	---------

**Technical data**

Description of article	Reel of wire end ferrules, grey	Version	insulated
------------------------	------------------------------------	---------	-----------

**Wire-end ferrules**

Collar diameter (D2)	4.3 mm	Colour code	Telemecanique
Conductor cross-section	2.5 mm <sup>2</sup>	Contact surface diameter (D1)	2.2 mm
Contact surface length (L2)	10 mm	L1 in mm	16 mm
Metal sleeve thickness (S1)	0.15 mm	Plastic collar thickness (S2)	0.28 mm
Stripping length	12 mm	Wire connection cross section AWG, max.	AWG 14

**Classifications**

ETIM 6.0	EC000005	ETIM 7.0	EC000005
ECLASS 9.0	27-40-02-01	ECLASS 9.1	27-40-02-01
ECLASS 10.0	27-40-02-01	ECLASS 11.0	27-40-02-01

**Approvals**

Approvals



ROHS	Conform
UL File Number Search	E499744

**Downloads**

Engineering Data	<a href="#">EPLAN</a>
User Documentation	<a href="#">Technical information - EN</a> <a href="#">Technical information - DE</a>

**Data sheet**

**H2,5/16T GR BD GSP**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Drawing**

