


HYBRID FEED-THROUGH TERMINAL,
3 CONNECT. POINTS,
WITH SPRING CONNECTION AND QUICK CONNECTION,
SECTION: 0.08 - 6 MM², WIDTH: 6.2 MM,
COLOR: BLUE



Similar to image

Technical data:

Operating current / rated value	A	24
Operating voltage / rated value	V	800
Mounting type		DIN rail 35 mm
Combustibility class acc. to UL 94		V0
Material / of the insulating body		Other
Design of the electrical connection		
• 1		spring-loaded terminal
• 2		insulation piercing connection
Design tested acc. to type of protection / EEx e		No
Product component / required / connection plate		No
Number of terminal levels		1
Number of terminal points / per terminal level		3
Design of terminal / terminal levels linked internally		No
Terminal contact spacing	mm	6.2
Position / of terminal		top
Height / with lowest-profile installation	mm	39.3
Color		blue
Length	mm	71.6

Ambient temperature		
• during operating	°C	-25 ... +55
Conductor cross-section that can be connected		
• solid	mm ²	6 ... 6
• multibrin	mm ²	6 ... 6
• finely stranded		
• without wire end processing	mm ²	4 ... 4
• with wire end processing	mm ²	4 ... 4

Certificates/approvals:

General Product Approval

Declaration of
Conformity

Shipping Approval



GL

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://eb.automation.siemens.com/mall/en/WW/Catalog/Product/8WH3103-2HF01>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WWW/view/en/8WH3103-2HF01/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WH3103-2HF01

CAX-Online-Generator

<http://www.siemens.com/cax>

last change:

Aug 4, 2014