

CD-K-A3M-1 TAP-OFF PLUG



Similar to image

General technical details:

Product designation		tap-off unit for CD-K busbar trunking system
Product-type designation		CD-K-A3M-1
Product function / phase selection		Yes
Operating current		
<ul style="list-style-type: none"> • for circuit 1 <ul style="list-style-type: none"> • at 50 Hz / for AC / rated value / maximum • at 60 Hz / for AC / rated value / maximum 	A A	16 16
Operating frequency		
<ul style="list-style-type: none"> • rated value 	Hz	50 ... 60
Operating voltage		
<ul style="list-style-type: none"> • at 50 Hz / at AC / rated value / maximum • at 60 Hz / at AC / rated value / maximum 	V V	400 400
Number of conductors / of the connection cable		3
Number of poles / of the outgoing feeder		3

Mechanical design:

Conductor cross section / of the connection cable	mm ²	1.5
Cable length / of the connection cable	m	0.8

Execution of short-circuit and overloading protection / in the outgoing unit		fuse base for one 8,5x31,5 mm cylinder fuses
Design of the outgoing unit		cable
Product component / locking		Yes
Length	mm	189
Width	mm	59
Height	mm	48
Color		grey white
RAL color number		RAL 9002

Ambient conditions:

Protection class IP	IP54
----------------------------	------

Further information:

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Global Industry Mall (Online ordering system)

<http://www.siemens.com/lowvoltage/mall>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<http://support.automation.siemens.com/WW/view/en/BVP:211198/all>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=BVP:211198

last change:

Jul 7, 2014