

**SLA BB 1R SW 1885****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Minor component, major effect:**

Clip-on attachment elements increase the mechanical resilience of the whole plug connection by

- securing the male connectors to the circuit board
- providing a vibration-proof connection between the sockets and the male connectors

Clip-on or pre-assembled - always the right solution:

- Hard-wearing, precise fitting dovetail joint
- Hard-wearing metal threaded inserts
- Suitable for all outlet directions

Maximum stability, minimum effort:

- Extremely resilient for frequent fastening operations
- Complete set for easy selection

The result: soldering points, contacts and overall module are more resilient against mechanical stress such as vibrations and tensile loads.

**General ordering data**

|              |   |
|--------------|---|
| Version      | PCB plug-in connector, Accessories, Mounting block, black, Number of poles: 1 |
| Order No.    | <a href="#">2200740000</a>  |
| Type         | SLA BB 1R SW 1885   |
| GTIN (EAN)   | 4008190963767   |
| Qty.         | 1 pc(s).  |
| Product data |   |

**SLA BB 1R SW 1885**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany

www.weidmueller.com

**Technical data**

**Dimensions and weights**

Net weight 0.741 g

**Material data**

|                                       |        |                                       |          |
|---------------------------------------|--------|---------------------------------------|----------|
| Colour                                | black  | Colour chart (similar)                | RAL 9011 |
| Storage temperature, min.             | -40 °C | Storage temperature, max.             | 70 °C    |
| Operating temperature, min.           | -50 °C | Operating temperature, max.           | 100 °C   |
| Temperature range, installation, min. | -25 °C | Temperature range, installation, max. | 100 °C   |

**Rated data acc. to IEC**

tested acc. to standard IEC 60664-1, IEC 61984

**Packing**

|            |      |           |      |
|------------|------|-----------|------|
| VPE length | 0 mm | VPE width | 0 mm |
| VPE height | 0 mm |           |      |

**Classifications**

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC002943    | ETIM 7.0    | EC002943    |
| ECLASS 9.0  | 27-44-04-92 | ECLASS 9.1  | 27-44-04-92 |
| ECLASS 10.0 | 27-44-04-92 | ECLASS 11.0 | 27-46-04-05 |

**Important note**

IPC conformity Conformity: The products are developed, manufactured and delivered according international recognized standards and norms and comply with the assured properties in the data sheet resp. fulfill decorative properties in accordance with IPC-A-610 "Class 2". Further claims on the products can be evaluated on request.

Notes

- Long term storage of the product with average temperature of 50 °C and average humidity 70%, 36 months

**Approvals**

Approvals



ROHS Conform