



SIMATIC,
 SPARE PART LITHIUM BATTERY 3.6V,
 1.5AH FOR PG 7XX AND TD17, OP17, OP25,
 OP27, OP35, OP37, TP27, TP37, OP/TP270,
 MP270, MP270B, MP370,
 C7-621/623/624/626 CONNECTING CABLE APPROX.
 210MM)

Installation type/mounting	
Wall mounting/direct mounting possible	Yes ; in HMI devices, battery compartment
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	3.6 V ; 1.6 Ah
Battery	
Design	
Special design	Yes ; 2/3 AA
Technology	
Lithium-ion	Yes ; SL-361
Standards, approvals, certificates	
CE mark	Yes
Ambient conditions	
Operating temperature	
Operating temperature range, min.	0 °C
Operating temperature range, max.	55 °C
Storage/transport temperature	
min.	-20 °C

max.	70 °C
Relative humidity	
Operation, max.	90 %
Dimensions	
Height	33 mm ; Length
Thickness	14.7 mm ; Diameter
Weights	
Weight without packaging	12 g
Scope of supply	
Delivery unit in items	1 ; incl. 220 mm connecting cable
Other	
Note:	for TD17, OP17, OP25, OP27, OP35, OP37, TP27, TP37, OP/TP270, MP 270, MP 270B, MP 370, C7-621, C7-623, C7-624, C7-626 and PG 7xx
Usable in the following products	
Product 1	6AV3017-1NE30*
Product 2	6AV3617-1JC*
Product 3	6AV3525-1EA*
Product 4	6AV3627-1JK00-0AX0
Product 5	6AV3627-1LK00-1AX0
Product 6	6AV3627-7JK00-0AX0
Product 7	6AV3627-6LK00-0AA0
Product 8	6AV3535-1F*
Product 9	6AV3535-1TA*
Product 10	6AV3637-1ML00*
Product 11	6AV3637-1LL00*
Product 12	6AV3627-1NK00*
Product 13	6AV3627-1QK00*
Product 14	6AV3627-1QL00-0AX0
Product 15	6AV3637-1PL00-0AX0
Product 16	6AV6542-0C*
Product 17	6AV6545-0C*
Product 18	6AV6545-0AH*
Product 19	6AV6545-0AG10-0AX0
Product 20	6AV6542-0A*
Status	Aug 7, 2014