

**PB-DP SUB-D****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

**General ordering data**

Version	SUB-D
Order No.	<a href="#">8395500000</a>
Type	PB-DP SUB-D
GTIN (EAN)	4008 190394646
Qty.	1 pc(s).

Creation date March 29, 2021 10:49:09 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## PB-DP SUB-D

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Depth	16 mm	Depth (inches)	0.63 inch
Height	47.4 mm	Height (inches)	1.866 inch
Net weight	44 g	Width	64.6 mm
Width (inches)	2.543 inch		

## Temperatures

Humidity	Max. 75% at +25°C, non-condensing
----------	-----------------------------------

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

## Technical specifications for sub-D connector

BUS interface	D-Sub 9-pole, Pin	BUS, cable interface	Screw connection
Data rate	12 MBit/s	Housing main material	PC UL 94 V-1
Humidity	Max. 75% at +25°C, non-condensing	Interlock	UNC4-40
Outgoing elbow	90°	Plug-in connector and pin assignment	In accordance with the PROFIBUS specification
Programming interface	No	Protection degree	IP40
Temperature range of housing	-25...+80 °C	Terminating resistor available	No

## Technical data customisable plug-in connectors

Cable diameter, max.	8 mm	Cable diameter, min.	4.5 mm
Housing main material	PC UL 94 V-1	Protection degree	IP40
Temperature range of housing	-25...+80 °C		

## Classifications

ETIM 6.0	EC001132	ETIM 7.0	EC001132
ECLASS 9.0	27-44-03-02	ECLASS 9.1	27-44-03-90
ECLASS 10.0	27-44-03-02	ECLASS 11.0	27-44-03-02

## Approvals

Approvals



ROHS

Conform