

## VG M16-K67 5-10

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)

### Similar to illustration



In addition to the extensive range of enclosures, Weidmüller offers a variety of cable glands for a wide range of applications.

The cable glands made of brass, plastic and stainless steel meet the most various IP protection classes to suit any industrial enclosure.

Depending on the series of cable glands and the application, the cable glands are approved and tested according to VDE, UL, UR, cULus, DNV GL or EN 45545.

### General ordering data

|            |  |
|------------|--|
| Version    | VG K (standard plastic cable gland), Cable glands, M 16, 10 mm, OD min. 5 - OD max. 10 mm, Polyamide 6 |
| Order No.  | <a href="#">1909680000</a>   |
| Type       | VG M16-K67 5-10  |
| GTIN (EAN) | 4032248536603  |
| Qty.       | 50 pc(s).  |

Creation date March 26, 2021 7:24:41 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## VG M16-K67 5-10

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Length     | 40 mm  | Length (inches) | 1.575 inch |
| Net weight | 9.08 g |                 |            |

## General information

|                                     |              |                                     |         |
|-------------------------------------|--------------|-------------------------------------|---------|
| AF size 1                           | 22 mm        | Cable glands                        | metric  |
| External thread                     | M 16         | Length of thread                    | 10 mm   |
| Material                            | Polyamide 6  | Operating temperature range, max.   | 100 °C  |
| Operating temperature range, min.   | -20 °C       | Outer cable diameter, max.          | 10 mm   |
| Outer cable diameter, min.          | 5 mm         | Pitch of thread                     | 1.5 mm  |
| Protection degree                   | IP67         | Seal insert                         | NBR     |
| Standards                           | EN/IEC 62444 | Tightening torque                   | 2.5 Nm  |
| Torque for cap nut, max.            | 3.5 Nm       | Torque for cap nut, min.            | 2.5 Nm  |
| Torque for connecting adapter, max. | 4.75 Nm      | Torque for connecting adapter, min. | 3.75 Nm |
| Torque for lock nut, max.           | 4.75 Nm      | Torque for lock nut, min.           | 3.75 Nm |
| UL 94 flammability rating           | V-2          |                                     |         |

## Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC000441    | ETIM 7.0    | EC000441    |
| ECLASS 9.0  | 27-14-44-32 | ECLASS 9.1  | 27-14-44-32 |
| ECLASS 10.0 | 27-14-44-32 | ECLASS 11.0 | 27-14-44-32 |

## Approvals

Approvals



ROHS

Conform

## Downloads

|                  |                              |
|------------------|------------------------------|
| Engineering Data | <a href="#">STEP</a>         |
| Engineering Data | <a href="#">EPLAN, WSCAD</a> |