



Main

Range of product	Modicon Quantum automation platform
Product or component type	AC discrete output modules
Discrete output number	16

Complementary

Discrete output type	Isolated
Group of channels	16 groups of 1 channel
Supply frequency	47...63 Hz
Voltage drop	1.5 V
Discrete output voltage	20...132 V AC
Addressing requirement	1 output word
Absolute maximum output	200 V during one cycle AC 156 V for 10 s AC
Maximum load current	4 A rms 20...132 V each point 4 A rms sum of four points, continuous 16 A rms per module 2 mA rms 115 V off state leakage/points 1 mA rms 48 V off state leakage/points 1 mA rms 24 V off state leakage/points
Surge current	<= 30 A during 3 cycles per point <= 30 A during 1 cycle per point <= 20 A during 2 cycles per point
DV/Dt	400 V/ms
Response time	<= 0.5 ms at state 1 to state 0 <= 0.5 ms at state 0 to state 1
Protection type	Internal by RC filter
Power dissipation	1.85 + (1.1 V x total module load current)
Associated fuse rating	5 A
Marking	CE
Local signalling	16 LEDs green input status 1 LED red external fault detected (F) 1 LED green bus communication is present (Active)
Bus current requirement	350 mA
Module format	Standard
Product weight	0.485 kg

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment


Product certifications	CUL FM Class 1 Division 2
Standards	CSA C22.2 No 142 UL 508
Electromagnetic compatibility	Susceptibility to electromagnetic fields (test level:10 V/m, 80...1000 MHz) conforming to IEC 801-3 Electrostatic discharge immunity test (test level:8 kV, air discharge) conforming to IEC 801-2 Electrostatic discharge immunity test (test level:4 kV, contact discharge) conforming to IEC 801-2
Ambient air temperature for operation	0...60 °C
Ambient air temperature for storage	-40...85 °C
Relative humidity	95 % without condensation
Operating altitude	<= 5000 m

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0901 - Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Need no specific recycling operations

Racks for Modules Mounting


Dimensions of Modules and Racks



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots

24...115 Vac Discrete Output Module

Wiring Diagram



N/C Not Connected