

## CLI C 2-4 GN/WS 5 MP

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

[www.weidmueller.com](http://www.weidmueller.com)



CLI C conductor markers are mounted on unconnected conductors. Four different sizes are available for labelling conductor cross-sections from 0.5 mm<sup>2</sup> to max. 70 mm<sup>2</sup>. The markers are already printed and ready for use. Individual labelling is possible by combining the individual markers.

- Closed markers, reliable and for mounting on unconnected cables
- A special flexible bellow profile ensures a wide application range
- Fast and easy to fit – with minimal effort
- Corresponding accessories make labelling easy
- Permanent, high-quality labelling
- High contrast for optimum legibility

### General ordering data

|            |  |
|------------|--|
| Version    | CableLine, Conductor and cable markers, 4 - 10 mm, {Reference (AttributeDefinition) not found: pAttr74196859207437}, green |
| Order No.  | <a href="#">0251311518</a>   |
| Type       | CLI C 2-4 GN/WS 5 MP   |
| GTIN (EAN) | 4032248452606  |
| Qty.       | 100 pc(s).   |

Creation date March 22, 2021 9:10:50 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## CLI C 2-4 GN/WS 5 MP

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

|                |            |                 |            |
|----------------|------------|-----------------|------------|
| Depth          | 8 mm       | Depth (inches)  | 0.315 inch |
| Height         | 4 mm       | Height (inches) | 0.157 inch |
| Net weight     | 0.16 g     | Width           | 7 mm       |
| Width (inches) | 0.276 inch |                 |            |

### Temperatures

|                             |             |
|-----------------------------|-------------|
| Operating temperature range | -30...80 °C |
|-----------------------------|-------------|

### General data

|                                   |  |  |               |
|-----------------------------------|--|--|---------------|
| Colour                            | green  | Colour of printing                           | white         |
| Halogen                           | Yes  | Insulation cross-section, max.               | 10 mm         |
| Material                          | PVC, soft, without Cadmium                     | Material colour according to resistance code | 5             |
| Number of markers per combination | 1 Component part = Conductor and cable markers | Operating temperature range                  | -30...80 °C   |
| Operating temperature range, max. | 80 °C  | Operating temperature range, min.            | -30 °C        |
| Orientation of print              | horizontal                                     | Printed characters                           | Numbers       |
| Printing                          | 5  | Printing method                              | hot-embossing |
| Recommended industries            | Process, Machinery                             | Type of printing                             | Standard      |
| UL 94 flammability rating         | V-0  | Version                                      | MultiPack     |
| Width                             | 7 mm   |  |               |

### Conductor and cable markers

|                               |                     |                                  |                          |
|-------------------------------|---------------------|----------------------------------|--------------------------|
| Conductor O.D.                | 4 - 10 mm           | Conductor O.D., max.             | 10 mm                    |
| Conductor O.D., min.          | 4 mm                | Conductor cross-section, max.    | 16 mm <sup>2</sup>       |
| Conductor cross-section, min. | 2.5 mm <sup>2</sup> | Cross-section for connected wire | 2.5 - 16 mm <sup>2</sup> |
| Halogen                       | Yes                 |                                  |                          |

### Classifications

|             |             |             |             |
|-------------|-------------|-------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0    | EC001530    |
| ECLASS 9.0  | 27-40-04-01 | ECLASS 9.1  | 27-40-04-01 |
| ECLASS 10.0 | 27-40-04-01 | ECLASS 11.0 | 27-28-11-02 |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                             |  |
|-----------------------------|--|
| Engineering Data            | <a href="#">EPLAN_WSCAD</a>  |
| Product Change Notification | <a href="#">PCN_CableLine_DE</a><br><a href="#">PCN_CableLine_EN</a> |