

**RS 32 24VUC LD LP 2U****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Similar to illustration

**General ordering data**

Version	RS-SERIES, Relay module, Number of contacts: 2, CO contact AgNi 90/10, Rated control voltage: 24 V UC $\pm 10\%$ , Continuous current: 4 A, Screw connection
Order No.	<a href="#">9406221001</a>
Type	RS 32 24VUC LD LP 2U
GTIN (EAN)	4032248046164
Qty.	10 pc(s).

Creation date March 30, 2021 1:03:04 AM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## RS 32 24VUC LD LP 2U

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

Depth	63.5 mm	Depth (inches)	2.5 inch
Height	70 mm	Height (inches)	2.756 inch
Net weight	45.18 g	Width	25 mm
Width (inches)	0.984 inch		

### Temperatures

Storage temperature	-40 °C...60 °C	Operating temperature	-25 °C...40 °C
Humidity	40 °C / 93 % rel. humidity, no condensation		

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

### Control side

Power rating	0.6 W / 0.9 VA	Protective circuit	Rectifier
Pull-in/drop-out current, typ.	2.5 mA AC 4.5 mA DC	Rated control voltage	24 V UC ± 10 %
Rated current AC	28 mA	Rated current DC	18 mA
Status indicator	red LED		

### Load side

AC switching capacity (resistive), max.	1000 VA	Duration of Bounce	≤ 4 ms
Inrush current	6 A	Max. switching frequency at rated load	0.1 Hz
Max. switching voltage, AC	250 V	Min. switching power	1 mA @ 24 V, 10 mA @ 10 V, 100 mA / 5 V DC
Switch-off delay	≤ 10 ms	Switch-on delay	≤ 13 ms

### Contact data

Contact type	2 CO contact (AgNi 90/10)	Mechanical service life	30 x 10 <sup>6</sup> switching cycles
--------------	---------------------------	-------------------------	---------------------------------------

### General data

Version	soldered relay	Rail	TS 32, TS 35
Test button	No	Mechanical switch position indicator	No
Colour	orange		

### Insulation coordination

Creepage and clearance distance input – output	> 3 mm	Dielectric strength to mounting rail	4 kV <sub>eff</sub> / 1 Min.
Impulse withstand voltage	4 kV (1.2/50 µs)	Pollution severity	2
Protection degree	IP20	Rated voltage	300 V
Surge voltage category	III		

### Further details of approvals / standards

Standards	DIN EN 50178	Certificate No. (CSA)	082859-C-000
-----------	--------------	-----------------------	--------------

Creation date March 30, 2021 1:03:04 AM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**RS 32 24VUC LD LP 2U****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Connection data**

Wire connection method	Screw connection	Stripping length, rated connection	8 mm
Clamping range, rated connection	2.5 mm <sup>2</sup>	Clamping range, min.	0.5 mm <sup>2</sup>
Clamping range, max.	4 mm <sup>2</sup>		

**Classifications**

ETIM 6.0	EC001437	ETIM 7.0	EC001437
ECLASS 9.0	27-37-16-01	ECLASS 9.1	27-37-16-01
ECLASS 10.0	27-37-16-01	ECLASS 11.0	27-37-16-01

**Approvals**

Approvals



ROHS

Conform

**Downloads**Approval/Certificate/Document of  
Conformity[DE\\_PA\\_5600\\_160311\\_001.pdf](#)

Engineering Data

[EPLAN, WSCAD](#)

**RS 32 24VUC LD LP 2U**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

Drawings

Wiring diagram

