

**IE-C7FS8LG-305M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

www.weidmueller.com



Bulk stock, copper cable, flexible, Cat. 7

**General ordering data**

Version	System cable, Cat.7 (ISO/IEC 11801), LSZH, 305 m
Order No.	<a href="#">1344680000</a>
Type	IE-C7FS8LG-305M
GTIN (EAN)	4050118146820
Qty.	1 pc(s).

Creation date March 23, 2021 4:47:16 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

## IE-C7FS8LG-305M

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

## Dimensions and weights

Length	305 m	Length (inches)	12,007.874 inch
Net weight	12,180 g		

## Temperatures

Storage temperature	-20 °C...60 °C	Operating temperature	-20 °C...60 °C
Installation temperature	0 °C...50 °C		

## Technical specifications for cable

Halogen	No	Insulation	PE
Number of wires	8	Resistance to spread of flame	in accordance with IEC 60332-1
Sheathing colour	green	Test voltage: wire-wire-shield	750 V DC, 1 min

## Cable specific standards

Generic communication cable facilities	ISO / IEC 11801:2002, EN 50173-1:2007	Impervious to smoke	to IEC 60754-2
--	---------------------------------------	---------------------	----------------

## General standards

Certificate no. (cULus)	E349758
-------------------------	---------

## Standards

Generic communication cable facilities	ISO / IEC 11801:2002, EN 50173-1:2007	Impervious to smoke	to IEC 60754-2
--	---------------------------------------	---------------------	----------------

## Cable structure

Arrangement of wire cores	Twisted pair	Colour sequence or wires - wire pairs	white - blue, white - orange, white - green, white - brown
Complete shielding	Shielding braid made from copper wiring	Copper diameter	0.43 mm
Cross-section	4*2*AWG 27/7 - 4*2*0.1 mm <sup>2</sup>	Insulation	PE
Insulation cross-section	1.04 mm	Material sheath	LSZH
Number of wires	8	Overlap of shielding braid	60 %
Sheath diameter, max.	5.9 mm	Sheath diameter, min.	5.5 mm
Sheathing colour	green	Shielding	S/FTP
Strands	7	Wire material	Non-insulated copper wire

## Electrical properties of cable

Capacity at 1 kHz	46 nF/km	Category	Cat.7 (ISO/IEC 11801)
Characteristic impedance	100 ± 15 Ω at 1-100 MHz	Deviation	25 ns/100m
Loop resistance	183 Ω/km	Resistance differential	5 %
Test voltage: wire-wire-shield	750 V DC, 1 min		

**IE-C7FS8LG-305M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Mechanical and material properties of cable**

Halogen	No	Impervious to smoke	to IEC 60754-2
Min. bending radius, once only	25 mm	Min. bending radius, repetitive	50 mm
Resistance to spread of flame	in accordance with IEC 60332-1		

**Classifications**

ETIM 6.0	EC000830	ETIM 7.0	EC003249
ECLASS 9.0	27-06-18-05	ECLASS 9.1	27-06-90-90
ECLASS 10.0	27-06-18-01	ECLASS 11.0	27-06-18-01

**Approvals**

Approvals



ROHS	Conform
UL File Number Search	E349758

**Downloads**

User Documentation	<a href="#">MAN IE GUIDE DE</a> <a href="#">MAN IE GUIDE EN</a>
--------------------	--

**Data sheet**

**IE-C7FS8LG-305M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Detailed drawing**

