

**CB-R 250/7.5 BLACK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Releasable and reusable cable ties, suitable for temporary bundling and when open-close function is necessary.

**General ordering data**

Version	Cable ties, {Reference (AttributeDefinition) not found: pAttr74196859207437}; {Reference (AttributeDefinition) not found: pAttr74196859207437}, Polyamide 66, 220 N
Order No.	<a href="#">1059230000</a>
Type	CB-R 250/7.5 BLACK
GTIN (EAN)	4032248806171
Qty.	100 pc(s).

Creation date March 22, 2021 9:26:26 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**CB-R 250/7.5 BLACK****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	2 mm	Depth (inches)	0.079 inch
Height	250 mm	Height (inches)	9.842 inch
Net weight	2.56 g	Width	7.5 mm
Width (inches)	0.295 inch		

**Temperatures**

Operating temperature range	-40...85 °C
-----------------------------	-------------

**Installation materials**

Cable diameter, max.	70 mm	For re-opening	Yes
Halogen	No	Material	Polyamide 66
Operating temperature range, max.	85 °C	Operating temperature range, min.	-40 °C
Tensile strength	220 N	UL 94 flammability rating	V-2
UV-resistant	No		

**Classifications**

ETIM 6.0	EC000046	ETIM 7.0	EC000046
ECLASS 9.0	27-14-07-02	ECLASS 9.1	27-14-07-02
ECLASS 10.0	27-14-07-02	ECLASS 11.0	27-14-07-02

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Approval/Certificate/Document of Conformity	<a href="#">DE P1830000 160627 001</a>
Engineering Data	<a href="#">EPLAN_WSCAD</a>

**Data sheet**

**CB-R 250/7.5 BLACK**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany

[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

**Drawing**

