



### Main

Range of product	ConneXium
Product or component type	Ethernet TCP/IP unmanaged switch
Concept	Transparent Ready
Communication port protocol	Ethernet TCP/IP
Port Ethernet	10BASE-T/100BASE-TX - 5 port(s) copper cable
Maximum number of switches in cascade	Unlimited

### Complementary

Integrated connection type	1 M12 port copper cable
Transmission support medium	Twisted shielded pairs cable CAT 5E for copper cable
Cable length	100 m copper cable
Ethernet service	Automatic negotiation of 10/100 Mbit/s and duplex mode Auto MDI/MDX Storage and re-routing of received data
[Us] rated supply voltage	24 V
Supply voltage limits	18...32 V DC SELV
Power consumption	3.2 W
Electrical connection	Removable M12 connector 5 ways power supply
Mounting support	35 mm symmetrical DIN rail
Marking	CE
Local signalling	1 LED per channel copper port activity 1 LED power supply
Ethernet cabling system	TF switches
Width	60 mm
Height	126 mm
Depth	31 mm
Product weight	0.21 kg

### Environment

Ambient air temperature for operation	0...60 °C
IP degree of protection	IP67
Standards	CSA C22.2 No 142 CUL 508

### Offer Sustainability

Sustainable offer status	Not Green Premium product
--------------------------	---------------------------