

CB 370/3.5 BLACK

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



CB cable ties for the fastening of cables and markers.

- They are particularly suitable for fastening CLI M, SFX, WKM and WKS cable markers
- IEC 62275: 2006-conformant
- Fracture-resistant polyamide PA 6.6 with flammability rating V2 to UL-94

General ordering data

Version	Cable ties, {Reference (AttributeDefinition) not found: pAttr74196859207437}; {Reference (AttributeDefinition) not found: pAttr74196859207437}, Polyamide 66, 130 N
Order No.	7940006057
Type	CB 370/3.5 BLACK
GTIN (EAN)	4032248520220
Qty.	100 pc(s).

Creation date March 29, 2021 10:28:16 PM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

CB 370/3.5 BLACK**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	1.5 mm	Depth (inches)	0.059 inch
Height	370 mm	Height (inches)	14.567 inch
Net weight	1.92 g	Width	3.6 mm
Width (inches)	0.142 inch		

Temperatures

Operating temperature range	-40...85 °C
-----------------------------	-------------

Installation materials

Cable diameter, max.	103 mm	For re-opening	No
Halogen	No	Material	Polyamide 66
Operating temperature range, max.	85 °C	Operating temperature range, min.	-40 °C
Tensile strength	130 N	UL 94 flammability rating	V-2
UV-resistant	No		

Classifications

ETIM 6.0	EC000046	ETIM 7.0	EC000046
ECLASS 9.0	27-14-07-02	ECLASS 9.1	27-14-07-02
ECLASS 10.0	27-14-07-02	ECLASS 11.0	27-14-07-02

Approvals

Approvals



ROHS	Conform
UL File Number Search	E317499

Downloads

Approval/Certificate/Document of Conformity	DE PI830000160627 002
Engineering Data	EPLAN, WSCAD

Data sheet

CB 370/3.5 BLACK

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

