



Main

| | |
|---------------------------|---------------------------------------|
| Range of product | Modicon TSX Micro automation platform |
| Product or component type | Analog input module |
| Number of channels | 8 |
| Analogue input type | 0...10 V |

Complementary

| | |
|---------------------------|----------------|
| Analog/Digital conversion | 11 bits + sign |
| Acquisition period | 32 ms |
| Temperature drift | 0.068 %/10 °C |
| Input impedance | 2.2 Ohm |
| Current consumption | 60 mA |
| Isolation voltage | 1000 V AC |
| Product weight | 0.2 kg |

Offer Sustainability

| | |
|--------------------------|---|
| Sustainable offer status | Not Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0908 - Schneider Electric declaration of conformity |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Wiring Diagram

