



### Main

Range of product	Modicon TSX Micro automation platform
Product or component type	Counter modules
Counting input number	1
Counting frequency	40 Hz
Network frequency	100 Hz
Input voltage	24 V DC 5 V DC
Input current	18 mA
Input voltage limits	<= 5 V at state 0 24 V DC >= 11 V at state 1 24 V DC <= 1.2 V at state 0 5 V DC >= 2.4 V at state 1 5 V DC 19...30 V 24 V DC 5.5 V 5 V DC
Input current limits	>= 3.7 mA at state 1 5 V DC <= 2 mA at state 0 24 V DC >= 6 mA at state 1 24 V DC <= 1 mA at state 0 5 V DC

### Complementary

Response time	8 ms master task 1.5 ms event processing
Sensor power supply	< 2.5 V
Current consumption	15 mA
Logic input	Positive
Input impedance	>= 0.44 Ohm 5 V DC at U = 2.4 V 1.4 Ohm 24 V DC at Un 0.27 Ohm 5 V DC at Un
Response time	3 ms
Input type	Resistive 24 V DC
Input compatibility	2-wire/3-wire proximity sensor 24 V DC
Product weight	0.2 kg

### Environment

Standards	IEC 1131 Type 2 24 V DC
-----------	-------------------------

### Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Will not be Compliant

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.