

H25,0/15**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



For conductors from 10.0 to 185.0 mm² (AWG 7 - 350 MCM)

tin-plated copper

dimensional tolerances to DIN 46228 part 1

- supplied loose in poly-bag

General ordering data

| | |
|------------|--------------------------------------|
| Version | Wire-end ferrule, uninsulated, 15 mm |
| Order No. | 0124400000 |
| Type | H25,0/15 |
| GTIN (EAN) | 4008190071790 |
| Qty. | 250 pc(s). |
| Packaging | loose |

Creation date March 22, 2021 8:50:03 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

H25,0/15

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 0.62 g

Technical data

| | | | |
|------------------------|---|---------|-------------|
| Description of article | Wire end ferrule without plastic collar | Version | uninsulated |
|------------------------|---|---------|-------------|

Wire-end ferrules

| | | | |
|-------------------------------|--------|---|--------------------|
| Collar diameter (D2) | 9.5 mm | Conductor cross-section | 25 mm ² |
| Contact surface diameter (D1) | 7.3 mm | L1 in mm | 15 mm |
| Stripping length | 15 mm | Wire connection cross section AWG, max. | AWG 3 |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000005 | ETIM 7.0 | EC000005 |
| ECLASS 9.0 | 27-40-02-01 | ECLASS 9.1 | 27-40-02-01 |
| ECLASS 10.0 | 27-40-02-01 | ECLASS 11.0 | 27-40-02-01 |

Approvals

Approvals



| | |
|-----------------------|---------|
| ROHS | Conform |
| UL File Number Search | E499744 |

Downloads

| | |
|------------------|--|
| Engineering Data | STEP |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |

Data sheet

H25,0/15

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

