

LIR 6M10 V**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Insulated ring-cable connector made from PVC**

- Commercially available designs
- Not soldered
- With conical entry funnel

General ordering data

Version	cable lug, terminal end, Insulated cable connector, 4 mm ² - 6 mm ²
Order No.	9200270000
Type	LIR 6M10 V
GTIN (EAN)	40322484 10095
Qty.	100 pc(s).

Creation date March 30, 2021 12:49:37 AM CEST

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

LIR 6M10 V

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Depth	8.1 mm	Depth (inches)	0.319 inch
Net weight	2.1 g	Width	35.1 mm
Width (inches)	1.382 inch		

Technical data

Description of article	Insulated ring-cable connector 6.0 mm ² / M10		
------------------------	--	--	--

Connectors

Conductor cross-section, max.	6 mm ²	Conductor cross-section, min.	4 mm ²
Connection density (S1)	1 mm	Dimension	M 10
Dimension (bolt)	M 10	Identification colour	yellow
Inside diameter (d1)	10.5 mm	Insulation	Available
Material/plastic	PVC	Outside diameter (d)	15 mm
Plastic collar diameter (D)	6.4 mm	Plastic collar length (b)	14.15 mm

Classifications

ETIM 6.0	EC001059	ETIM 7.0	EC001059
ECLASS 9.0	27-40-02-92	ECLASS 9.1	27-40-02-12
ECLASS 10.0	27-40-02-92	ECLASS 11.0	27-40-02-92

Approvals

Approvals



ROHS Conform

Downloads

Engineering Data [EPLAN](#)