

IE-BI-LCD-MM-C**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



FO LC inserts for plug-in connectors ver.1 / 4 / 14

General ordering data

Version	LC insert, Bulkhead insert LC duplex, multimode
Order No.	1964420000
Type	IE-BI-LCD-MM-C
GTIN (EAN)	4032248649037
Qty.	10 pc(s).

Creation date March 26, 2021 3:46:15 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

IE-BI-LCD-MM-C**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	30 mm	Depth (inches)	1.181 inch
Height	13.2 mm	Height (inches)	0.52 inch
Net weight	14.1 g	Width	15.6 mm
Width (inches)	0.614 inch		

Temperatures

Operating temperature	-40 °C...70 °C	Humidity	0...85 % rel. humidity
-----------------------	----------------	----------	------------------------

General data

Colour	Miscellaneous	Configuration	Connector and flange insert for variant 1, 4 and 14 housings
Connection 1	LC Duplex	Connection 2	gluing, crimping, polishing
Description of article	Bulkhead insert LC duplex, multimode	Fibre type	Multimode
Housing main material	PBT diecast zinc	Humidity	0...85 % rel. humidity
Insertion loss	≤ 0.4 dB	Plugging cycles	1000
Protection degree	IP67 with housing	Return loss (attenuation)	≥ 30 dB

General standards

Connector standard	IEC 61754-20
--------------------	--------------

Classifications

ETIM 6.0	EC001122	ETIM 7.0	EC001122
ECLASS 9.0	19-17-01-22	ECLASS 9.1	19-17-01-22
ECLASS 10.0	19-17-01-22	ECLASS 11.0	19-17-01-22

Approvals

ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	GOST Approval
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN Designation key / Type key

IE-BI-LCD-MM-C

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

Dimensioned drawing

