

CMA-RCM-DACT-20**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration

For detection of residual currents in 3- / 4-wire AC systems.

Features:

- High-sensitive current sensor for detecting even smallest fault currents
- Fixed hysteresis at 5%
- High security due to integrated overvoltage protection
- Wide frequency range

General ordering data

Version	Residual current transformer, Primary current: 25 A, Round conductor: 20.00 mm, closed current transformer
Order No.	2603420000
Type	CMA-RCM-DACT-20
GTIN (EAN)	4050118665420
Qty.	1 pc(s).

Creation date April 16, 2021 4:37:01 AM CEST

Catalogue status 09.04.2021 / We reserve the right to make technical changes.

CMA-RCM-DACT-20**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

Depth	30 mm	Depth (inches)	1.181 inch
Height	63 mm	Height (inches)	2.48 inch
Net weight	240 g	Width	82 mm
Width (inches)	3.228 inch		

Temperatures

Storage temperature	-25 °C...70 °C	Operating temperature	-10 °C...70 °C
---------------------	----------------	-----------------------	----------------

Measuring current input

Residual current measuring	Yes
----------------------------	-----

Dimensions of live conductors

Installation location	Indoor use	Round conductor	20 mm
Type of conductor	Insulated conductor only		

Electrical attributes

Frequency band	30 Hz...3 kHz	Load	0 VA
Primary current	25 A	Secondary current	0...41.7 mA
Secondary current max.	0.04 A	Secondary current, min.	0.042 A
Tolerance class	1	Transmission ratio	1:600

Technical data

Pollution severity	3	Protection degree	IP40
Standards	EN 61010-1, EN 61000-6-1:2007, EN 61000-6-3:2007	Residual current measuring	Yes

Input

Input measurement range	0.02...2 A / 0.25...25 A depending on terminal assignment
-------------------------	---

Insulation coordination

Galvanic isolation	yes	Impulse withstand voltage	8 kV
Pollution severity	3	Rated voltage	800 V
Standard	EN 60044/1	Tolerance class	1

Classifications

ETIM 6.0	EC002048	ETIM 7.0	EC002048
ECLASS 9.0	27-21-09-02	ECLASS 9.1	27-21-09-02
ECLASS 10.0	27-21-09-02	ECLASS 11.0	27-21-09-02

Approvals

ROHS	Conform
------	---------

CMA-RCM-DACT-20

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Downloads

User Documentation	Instruction sheet
Brochure/Catalogue	Catalogues in PDF-format
