

TBF 60/60/18 7035

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration



The enclosures of the TBF series are made of extremely tough glass fibre-reinforced polyester. These enclosures are ideal for applications that call for low weight coupled with high shock resistance. The weather-resistant TBF enclosures are designed for a wide range of applications. Together with their comprehensive range of accessories, they provide universal solutions for accommodating built-in items such as regulators, measuring instruments, valves and other equipment.

Features:

- 9 sizes in 2 versions, with grey and transparent lids
- Cover with nylon screws
- Fixing holes outside the sealed area
- Thread for fitting to terminal rails and mounting plates
- Comprehensive accessories
- Weidmüller can manufacture and supply this enclosure to match customer specifications, fitted with all necessary terminals and cable glands.

General ordering data

| | |
|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Version | TBF (polyester empty enclosure), Empty enclosure, Height: 603 mm, Width: 605 mm, Depth: 175 mm, Material: Glass fibre-reinforced polyester, Light Grey |
| Order No. | 9502830000 |
| Type | TBF 60/60/18 7035 |
| GTIN (EAN) | 4032248371143 |
| Qty. | 1 pc(s). |

TBF 60/60/18 7035

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|-------------|
| Depth | 175 mm | Depth (inches) | 6.89 inch |
| Height | 603 mm | Height (inches) | 23.74 inch |
| Net weight | 7,720 g | Weight | 7,400 g |
| Width | 605 mm | Width (inches) | 23.819 inch |

Cable glands, right

| | | | |
|-----|----|-----|----|
| M12 | 88 | M16 | 48 |
| M20 | 40 | M25 | 20 |
| M32 | 8 | M40 | 6 |
| M50 | 6 | M63 | 4 |

Cable glands, top/bottom

| | | | |
|-----|----|-----|----|
| M12 | 88 | M16 | 48 |
| M20 | 40 | M25 | 20 |
| M32 | 8 | M40 | 6 |
| M50 | 6 | M63 | 4 |

Certificate numbers enclosure

| | | | |
|-----------------------|---------------------|------------------------------------|-------------------------------------------|
| Certificate No. (EAC) | RUC-DE.BE02.B.00173 | Certificate no. Terminal Box (EAC) | RU C-DE.BE02.B.00173 Ind. Terminal Box |
|-----------------------|---------------------|------------------------------------|-------------------------------------------|

General information

| | | | |
|-----------------------------|-------------------------------------------------------------------------------------------|-----------------------------|----------------------------------------------------------------------|
| Access opening: height | 578 mm | Access opening: width | 578 mm |
| Areas of use | Building systems and technology, Transportation, Packaging industry, Machine construction | Enclosure attachment | 6.5 mm hole in enclosure base |
| Flange plate | No | Impact resistance | IK08 in accordance with IEC 62208, IK10 in accordance with IEC 62262 |
| Integral fixing | 4 or 6 stud bolts M6 inner (female) thread | Lid | Yes |
| Lid attachment | Crosshead nylon screws | Material | Glass fibre-reinforced polyester |
| Operating temperature, max. | 130 °C | Operating temperature, min. | -50 °C |
| Protection degree | IP67 | Seal material | Polyurethane |
| Standards | IEC 60529, EN 60529, EN 62208, EN/IEC 61439-2 | Torque for lid screws | 1.5 Nm |
| Toxicity | Free from halogens | UL 94 flammability rating | HB |

horizontal assembly

| | | | |
|-----------------------------|-------|-----------------|------|
| WDU 10 / ZDU 10 | 4x51 | WDU 16 / ZDU 16 | 4x37 |
| WDU 2,5 / ZDU 2,5 / IDU 2,5 | 4x101 | WDU 35 / ZDU 35 | 4x32 |
| WDU 4 / ZDU 4 | 4x85 | WDU 6 / ZDU 6 | 4x64 |

vertical assembly

| | | | |
|-----------------------------|-------|-----------------|------|
| WDU 10 / ZDU 10 | 5x51 | WDU 16 / ZDU 16 | 5x37 |
| WDU 2,5 / ZDU 2,5 / IDU 2,5 | 5x101 | WDU 35 / ZDU 35 | 5x32 |
| WDU 4 / ZDU 4 | 5x85 | WDU 6 / ZDU 6 | 5x64 |

Creation date March 30, 2021 2:24:00 AM CEST

TBF 60/60/18 7035

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000261 | ETIM 7.0 | EC000261 |
| ECLASS 9.0 | 27-18-01-01 | ECLASS 9.1 | 27-18-92-90 |
| ECLASS 10.0 | 27-18-01-01 | ECLASS 11.0 | 27-18-01-01 |

Approvals

Approvals



ROHS Conform

Downloads

| | |
|---------------------------------------------|----------------------------------------------------------|
| Approval/Certificate/Document of Conformity | RU C-DE.BE02.B.00173 - Ind. Terminal Box |
| Engineering Data | STEP |
| Engineering Data | EPLAN, WSCAD |

Drawings

