

VG M25 - MS 1/EMV

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Similar to illustration



Produktabbildung

The increasing sensitivity of electronic components and the increasing electromagnetic interference frequencies require cable glands to play an important role in the shielding concept of a system. This type of EMC cable glands are made for shielding against interference frequencies, with a 360° screening connection. A Finger-locking seal provides superior cable retention & strain relief, next to it, the cable gland meets the mechanical requirements of EN 62444. Due to the patented design a very easy and fast assembly will be possible.

General ordering data

Version	VG EMV GEN 1 (EMC cable gland with clamping cage), Cable glands, M 25, 8, OD min. 11 - OD max. 17 mm, IP68 - 5 bar (30 min.), IP69K, Brass, nickel-plated
Order No.	1909520000
Type	VG M25 - MS 1/EMV
GTIN (EAN)	4032248536443
Qty.	25 pc(s).

Creation date March 26, 2021 7:24:08 AM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

VG M25 - MS 1/EMV

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data

Dimensions and weights

Length	38.7 mm	Length (inches)	1.524 inch
Net weight	50.64 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Certificate numbers cable gland

Approval conditions	DNV, UL, cULus	Certificate no. cable gland (GERMLLOYD)	E-14047
Certificate no. cable gland (UL)	E-199260	Certificate no. cable gland (cULus)	E-199260

General information

AF size 1	27 mm	Cable glands	metric
Clamp insert	Polyamide	External thread	M 25
Length of thread	8 mm	Material	Brass, nickel-plated
O-Ring	NBR	Operating temperature range, max.	100 °C
Operating temperature range, min.	-40 °C	Outer cable diameter, max.	17 mm
Outer cable diameter, min.	11 mm	Pitch of thread	1.5 mm
Protection degree	IP68 - 5 bar (30 min.), IP69K	Protection degree with GWDR	IP68 - 5 bar (30 min.), IP69K
Seal insert	CR	Sealing	NBR
Shield diameter, max.	17 mm	Shield diameter, min.	9.5 mm
Tightening torque	8 Nm	Torque for cap nut, max.	8 Nm
Torque for cap nut, min.	6 Nm	Torque for connecting adapter, max.	12 Nm
Torque for connecting adapter, min.	9 Nm		

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
ECLASS 9.0	27-14-44-32	ECLASS 9.1	27-14-44-32
ECLASS 10.0	27-14-44-32	ECLASS 11.0	27-14-44-32

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Engineering Data	STEP
Engineering Data	EPLAN, WSCAD

Data sheet

VG M25 - MS 1/EMV

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

