

**ZVR 3****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image****Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

**General ordering data**

Version	Accessories, Plug-in connector
Order No.	<a href="#">1718700000</a>
Type	ZVR 3
GTIN (EAN)	4008 190386047
Qty.	20 pc(s).

Creation date March 24, 2021 10:24:46 PM CET

Catalogue status 12.03.2021 / We reserve the right to make technical changes.

**ZVR 3****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Technical data****Dimensions and weights**

Depth	4.01 mm	Depth (inches)	0.158 inch
Height	32.75 mm	Height (inches)	1.289 inch
Net weight	0.47 g	Width	9.2 mm
Width (inches)	0.362 inch		

**Temperatures**

Storage temperature	-25 °C...55 °C	Continuous operating temp., min.	-50
Continuous operating temp., max.	120		

**Material data**

Material	Wemid	Colour	Traffic grey (RAL)
UL 94 flammability rating	V-0		

**System specifications**

Version	Latches
---------	---------

**Additional technical data**

Installation advice	Direct mounting
---------------------	-----------------

**Conductors for clamping (rated connection)**

Type of connection	Plug-in connection
--------------------	--------------------

**General**

Installation advice	Direct mounting
---------------------	-----------------

**Classifications**

ETIM 6.0	EC002848	ETIM 7.0	EC002848
ECLASS 9.0	27-14-11-92	ECLASS 9.1	27-14-11-92
ECLASS 10.0	27-14-11-92	ECLASS 11.0	27-14-11-92

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">WSCAD</a>
User Documentation	<a href="#">StorageConditionsTerminalBlocks</a>