

PRODUCT-DETAILS

# 332QC9W

## Ind. P&S#332QC9W



### General Information

Extended Product Type	332QC9W
Product ID	2CMA102947R1000
EAN	7392696029476
Catalog Description	Ind. P&S#332QC9W
Long Description	Connector, earthing sleeve position 9h, rated current 32A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Blue, Screwless terminals

### Ordering

EAN	7392696029476
Country of Origin	Turkey (TR)
Minimum Order Quantity	5 piece

### Dimensions

Product Net Width	102 mm
Product Net Height	102 mm
Product Net Weight	0.308 kg

---

**Container Information**


---

Package Level 1 Width	190 mm
Package Level 1 Depth / Length	265 mm
Package Level 1 Height	230 mm
Package Level 1 Gross Weight	1.881 kg
Package Level 1 EAN	7392696042871
Package Level 1 Units	box 5 piece

---

**Environmental**


---

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---

**Certificates and Declarations (Document Number)**


---

Declaration of Conformity - CE	2CMC700005D0001
Environmental Information	2CMC000072M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

---

**Additional Information**


---

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm <sup>2</sup>
Cable Diameter	11 ... 20.5 mm
Cable Entry Position	Swivel
Color	Blue
Connection Type	Screwless
Degree of Protection	IP67
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332QC9W
Number of Poles	4
Order Multiple	5 piece
Product Main Type	QC
Product Name	Industrial Connector
Protection Type	Watertight
Rated Current (I <sub>n</sub> )	32 A
Rated Voltage (U <sub>r</sub> )	200 ... 250 V
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instructions and Manuals	2CMC700014C0016

RAL Number

RAL 7012 - Basalt Grey

---

### Classifications

---

eClass

27440509

UNSPSC

39120000

---

---

### Categories

---

Low Voltage Products and Systems → Industrial Plugs and Sockets → Fast & Safe

