



PRODUCT-DETAILS

TY5424PX

CABLE TIE 150LB 24IN UV BLK PP LASH



General Information

Extended Product Type	TY5424PX
Product ID	7TAG009550R0022
EAN	5414363066422
Catalog Description	CABLE TIE 150LB 24IN UV BLK PP LASH
Long Description	Lashing Cable Tie, Black Polypropylene for Temperatures up to 110 Degrees Celsius (230 F), Weather and Ultraviolet Resistant for Indoor and Outdoor Applications, UL/EN/CSA62275 Type 2/215 Rated for AH-2 Plenum and as a Flexible Cable and Conduit Support, Length of 610mm (24.02 Inches), Width of 13.2mm (0.52 Inches), Thickness of 1.8mm (0.07 Inches), Tensile Strength Rating of 670 Newtons (150 Pounds)

Ordering

EAN	5414363066422
-----	---------------

Dimensions

Product Net Width	0.52 in 13.2 mm
Product Net Length	0, mm
Product Net Depth / Length	24.02 in 610 mm

Container Information

Package Level 1 Units	25 piece
Package Level 2 Units	250 piece
Package Level 2 Width	11.5 in 292 mm
Package Level 2 Height	6.5 in 165 mm
Package Level 2 Depth / Length	29 in 737 mm

Additional Information

Brand / Label	Ty-Rap
Bundle Diameter	0.39 to 7 in 10 to 1.78 mm
Color	Black
Effective Date	19770222
Lock Type	Plastic Closing Mechanism
Material	Polypropylene
Number of Batteries	0
Product Name	TY-RAP FASTENING
Product Type	Lashing
Special Functions	Chemical exposure directly affects the life of a cable tie making polypropylene ties an ideal choice. Black is usable for outdoor use, too.
Tensile Strength	150 lb 670 N
Thickness	0.07 in 1.8 mm
UPC	786210888170

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TY5424PX
Instructions and Manuals	TY5424PX

Classifications

ETIM 6	EC000046 - Cable tie
ETIM 7	EC000046 - Cable tie
UNSPSC	39121703
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5034 >> Cable ties

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Cable Ties

