

## PRODUCT-DETAILS

# AFS96-30-22-11

## AFS96-30-22-11 24-60V50/60HZ 20-60VDC Contactor



### General Information

|                       |                                                 |
|-----------------------|-------------------------------------------------|
| Extended Product Type | AFS96-30-22-11                                  |
| Product ID            | 1SBL407082R1122                                 |
| EAN                   | 3471523158016                                   |
| Catalog Description   | AFS96-30-22-11 24-60V50/60HZ 20-60VDC Contactor |

|                  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Long Description | <p>AFS40 ... AFS96 contactors are designed for machine safety applications. They are delivered with fixed front-mounted auxiliary contact blocks making them ideal for monitoring and controlling circuits. Mechanically linked and mirror contacts make your system safer. - control circuit with electronic coil interface: - 24...60 V AC, 20...60 V DC and 100...250 V AC / DC operated accepting a wide control voltage range - reduced panel energy consumption - mirror and mechanically linked contacts, with front marked symbol acc. to IEC60947-5-1, always guaranteeing the right contactor status - front-mounted auxiliary contact block: - permanently fixed - protective cover to prevent manual operation - yellow housing for easy identification - minimum switching capacity 12 V / 3 mA, with a failure rate 10<sup>-7</sup> acc. to IEC 60947-5-4 - built-in surge suppression</p> |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

### Ordering

|                        |          |
|------------------------|----------|
| Minimum Order Quantity | 1 piece  |
| Customs Tariff Number  | 85364900 |

### Popular Downloads

|                          |                 |
|--------------------------|-----------------|
| Instructions and Manuals | 1SBC101052M6801 |
|--------------------------|-----------------|

## Dimensions

|                            |          |
|----------------------------|----------|
| Product Net Width          | 70 mm    |
| Product Net Depth / Length | 149 mm   |
| Product Net Height         | 125.5 mm |
| Product Net Weight         | 1.27 kg  |

## Technical

|                                                    |                                                                                                                                                                                                                                                                                                                                                                                         |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of Main Contacts NO                         | 3                                                                                                                                                                                                                                                                                                                                                                                       |
| Number of Main Contacts NC                         | 0                                                                                                                                                                                                                                                                                                                                                                                       |
| Number of Auxiliary Contacts NO                    | 2                                                                                                                                                                                                                                                                                                                                                                                       |
| Number of Auxiliary Contacts NC                    | 2                                                                                                                                                                                                                                                                                                                                                                                       |
| Rated Operational Voltage                          | Auxiliary Circuit 690 V<br>Main Circuit 1000 V                                                                                                                                                                                                                                                                                                                                          |
| Rated Frequency (f)                                | Auxiliary Circuit 50 / 60 Hz<br>Main Circuit 50 / 60 Hz                                                                                                                                                                                                                                                                                                                                 |
| Conventional Free-air Thermal Current ( $I_{th}$ ) | acc. to IEC 60947-4-1, Open Contactors q = 40 °C 130 A<br>acc. to IEC 60947-5-1, q = 40 °C 16 A                                                                                                                                                                                                                                                                                         |
| Rated Operational Current AC-1 ( $I_e$ )           | (690 V) 40 °C 130<br>(690 V) 60 °C 105 A<br>(690 V) 70 °C 90                                                                                                                                                                                                                                                                                                                            |
| Rated Operational Current AC-3 ( $I_e$ )           | (415 V) 60 °C 96 A<br>(440 V) 60 °C 96 A<br>(500 V) 60 °C 80 A<br>(690 V) 60 °C 57 A<br>(1000 V) 60 °C 30 A<br>(380 / 400 V) 60 °C 96 A<br>(220 / 230 / 240 V) 60 °C 96 A                                                                                                                                                                                                               |
| Rated Operational Power AC-3 ( $P_e$ )             | (400 V) 45 kW<br>(415 V) 55 kW<br>(440 V) 55 kW<br>(500 V) 55 kW<br>(690 V) 55 kW<br>(380 / 400 V) 45 kW<br>(220 / 230 / 240 V) 25 kW                                                                                                                                                                                                                                                   |
| Rated Operational Current AC-15 ( $I_e$ )          | (500 V) 2 A<br>(690 V) 2 A<br>(24 / 127 V) 6 A<br>(220 / 240 V) 4 A<br>(400 / 440 V) 3 A                                                                                                                                                                                                                                                                                                |
| Rated Short-time Withstand Current ( $I_{cw}$ )    | at 40 °C Ambient Temp, in Free Air, from a Cold State 10 s 780 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 15 min 140 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 min 300 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 1 s 1200 A<br>at 40 °C Ambient Temp, in Free Air, from a Cold State 30 s 450 A<br>for 0.1 s 140 A<br>for 1 s 100 A |
| Maximum Breaking Capacity                          | cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 440 V 1150 A<br>cos phi=0.45 (cos phi=0.35 for $I_e > 100$ A) at 690 V 750 A                                                                                                                                                                                                                                                           |
| Maximum Electrical Switching Frequency             | (AC-1) 600 cycles per hour<br>(AC-15) 1200 cycles per hour<br>(AC-2 / AC-4) 150 cycles per hour<br>(AC-3) 1200 cycles per hour<br>(DC-13) 900 cycles per hour                                                                                                                                                                                                                           |
| Rated Operational Current DC-13 ( $I_e$ )          | (24 V) 6 A / 144 W<br>(48 V) 2.8 A / 134 W<br>(72 V) 1 A / 72 W<br>(110 V) 0.55 A / 60 W<br>(125 V) 0.55 A / 69 W<br>(220 V) 0.27 A / 60 W<br>(250 V) 0.27 A / 68 W                                                                                                                                                                                                                     |

|                                                     |                                                                                                                                                                                                                                                                           |
|-----------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                                     | (400 V) 0.15 A / 60 W<br>(500 V) 0.13 A / 65 W<br>(600 V) 0.1 A / 60 W                                                                                                                                                                                                    |
| Rated Insulation Voltage (U <sub>i</sub> )          | acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V<br>acc. to UL/CSA 600 V                                                                                                                                                                                                 |
| Rated Impulse Withstand Voltage (U <sub>imp</sub> ) | 8 kV                                                                                                                                                                                                                                                                      |
| Maximum Mechanical Switching Frequency              | 3600 cycles per hour                                                                                                                                                                                                                                                      |
| Rated Control Circuit Voltage (U <sub>c</sub> )     | 50 Hz 24 ... 60 V<br>50 Hz / 60 Hz 24 ... 60 V<br>60 Hz 24 ... 60 V<br>DC Operation 20 ... 60 V                                                                                                                                                                           |
| Operate Time                                        | Between Coil De-energization and NC Contact Closing 19 ... 105 ms<br>Between Coil De-energization and NO Contact Opening 17 ... 100 ms<br>Between Coil Energization and NC Contact Opening 38 ... 95 ms<br>Between Coil Energization and NO Contact Closing 42 ... 100 ms |
| Connecting Capacity Main Circuit                    | Flexible with Ferrule 1/2x 6 ... 50 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1/2x 6 ... 50 mm <sup>2</sup><br>Rigid 1x 6 ... 70 mm <sup>2</sup><br>Rigid 2x 6 ... 50 mm <sup>2</sup>                                                                            |
| Connecting Capacity Auxiliary Circuit               | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>                                     |
| Connecting Capacity Control Circuit                 | Flexible with Ferrule 1/2x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm <sup>2</sup><br>Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm <sup>2</sup><br>Rigid 1/2x 1 ... 2.5 mm <sup>2</sup>                                     |
| Wire Stripping Length                               | Auxiliary Circuit 10 mm<br>Control Circuit 10 mm<br>Main Circuit 17 mm                                                                                                                                                                                                    |
| Degree of Protection                                | acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20<br>acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10                                                                         |
| Terminal Type                                       | Screw Terminals                                                                                                                                                                                                                                                           |

## Technical UL/CSA

|                           |                                                                                                                                                                                                                                   |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General Use Rating UL/CSA | (600 V AC) 115 A                                                                                                                                                                                                                  |
| Horsepower Rating UL/CSA  | (120 V AC) Single Phase 7-1/2 hp<br>(200 ... 208 V AC) Three Phase 30 hp<br>(220 ... 240 V AC) Three Phase 30 hp<br>(240 V AC) Single Phase 20 hp<br>(440 ... 480 V AC) Three Phase 60 hp<br>(550 ... 600 V AC) Three Phase 75 hp |
| Tightening Torque UL/CSA  | Auxiliary Circuit 11 lA<br>Control Circuit 11 lA<br>Main Circuit 53 lA                                                                                                                                                            |

## Environmental

|                                                |                                                                                                                                                                                 |
|------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Ambient Air Temperature                        | Close to Contactor Fitted with Thermal O/L Relay -25 ... +60 °C<br>Close to Contactor without Thermal O/L Relay -40 ... +70 °C<br>Close to Contactor for Storage -60 ... +80 °C |
| Climatic Withstand                             | Category B according to IEC 60947-1 Annex Q                                                                                                                                     |
| Maximum Operating Altitude Permissible         | 3000 m                                                                                                                                                                          |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5 ... 300 Hz 3 g closed position / 3 g open position                                                                                                                            |
| Resistance to Shock acc. to IEC 60068-2-27     | Closed, Shock Direction: A 25 K40<br>Closed, Shock Direction: B1 25 K40<br>Closed, Shock Direction: B2 15 K40<br>Closed, Shock Direction: C1 25 K40                             |

Closed, Shock Direction: C2 25 K40

RoHS Status

Following EU Directive 2011/65/EU

### Certificates and Declarations (Document Number)

|                                    |                          |
|------------------------------------|--------------------------|
| BV Certificate                     | BV_2634H36994A           |
| CB Certificate                     | CB_SE-96557              |
| CCC Certificate                    | CCC_2013010304646569     |
| CQC Certificate                    | CQC2013010304646569      |
| cUL Certificate                    | UL_20170607-E312527-14-1 |
| Declaration of<br>Conformity - CCC | 2020980304001255         |
| Declaration of<br>Conformity - CE  | 1SBD250022U1000          |
| DNV Certificate                    | DNV-GL_TAE00001AF-3      |
| DNV GL Certificate                 | DNV-GL_TAE00001AF-3      |
| EAC Certificate                    | EAC_RUC-FRME77B03199     |
| GL Certificate                     | DNV-GL_TAE00001AF-3      |
| Instructions and<br>Manuals        | 1SBC101052M6801          |
| RMRS Certificate                   | RMRS_1802705280          |
| RoHS Information                   | 1SBD250022U1000          |
| UL Listing Card                    | E312527                  |

### Container Information

|                                   |               |
|-----------------------------------|---------------|
| Package Level 1 Units             | box 1 piece   |
| Package Level 1 Width             | 167 mm        |
| Package Level 1 Depth /<br>Length | 180 mm        |
| Package Level 1 Height            | 97 mm         |
| Package Level 1 Gross<br>Weight   | 1.41 kg       |
| Package Level 1 EAN               | 3471523158016 |
| Package Level 2 Units             | box 6 piece   |
| Package Level 2 Width             | 250 mm        |
| Package Level 2 Depth /<br>Length | 300 mm        |
| Package Level 2 Height            | 300 mm        |
| Package Level 2 Gross<br>Weight   | 8.46 kg       |
| Package Level 3 Units             | 144 piece     |

### Classifications

|                               |                                           |
|-------------------------------|-------------------------------------------|
| Object Classification<br>Code | Q                                         |
| ETIM 4                        | EC000066 - Magnet contactor, AC-switching |
| ETIM 5                        | EC000066 - Magnet contactor, AC-switching |
| ETIM 6                        | EC000066 - Power contactor, AC switching  |
| ETIM 7                        | EC000066 - Power contactor, AC switching  |
| eClass                        | V11.0 : 27371003                          |
| UNSPSC                        | 39121529                                  |
| E-Number (Finland)            | 3708061                                   |
| E-Number (Sweden)             | 3210675                                   |

---

## Categories

---

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

