

PRODUCT-DETAILS

EXLB0430

FLEX CONDUIT 20MM OIL RESISTANT 30M



General Information

Extended Product Type	EXLB0430
Product ID	7TCA297120R0070
EAN	5011949001138
Catalog Description	FLEX CONDUIT 20MM OIL RESISTANT 30M
Long Description	Liquid Tight Metallic Conduit, Oil and Dilute Acid Resistant, Conduit Size 20mm, Minimum Bore 16mm, Reel Length 30 Meters, Galvanised Steel Core with Flame Retardant PVC Covering, Black

Additional Information

Application	Connection for Conduit Systems when Oil and Acid Resistance is Needed
Product Type	Liquid Tight Metallic Conduit

Ordering

EAN	5011949001138
UPC	786210287416
Customs Tariff Number	8307106000

Dimensions

Product Net Depth / Length	30 m
----------------------------	------

Technical	
Number of Batteries	0
Color	Black
Material	Galvanized Steel Core with Flame Retardant PVC Covering

Environmental	
WEEE Category	Product Not in WEEE Scope

Container Information	
Package Level 1 Units	1 piece
Package Level 1 Height	5.9 in 150 mm
Package Level 1 Depth / Length	16.1 in 409 mm
Package Level 1 Width	16.1 in 409 mm
Package Level 2 Units	16 piece

Certificates and Declarations (Document Number)	
Data Sheet, Technical Information	EXLB0430
Instructions and Manuals	EXLB0430
Declaration of Conformity - CE	9AKK107492A9617

Classifications	
UNSPSC	39131706

Categories	
Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems	

