



PRODUCT-DETAILS

TBM6700

MID WALL 3:1 ADHES.LINED



General Information

Extended Product Type	TBM6700
Product ID	7TCA017410R0019
EAN	5414363109501
Catalog Description	MID WALL 3:1 ADHES.LINED
Long Description	Heat Shrink Tubing, Rated for 600 Volts, 90 Degree C, Continuous Use, RoHS Compliance, 170.2mm Expanded, 1 Per Bag, Black, Medium Wall, Adhesive Liner

Ordering

E-Number (Finland)	5240654
EAN	5414363109501

Dimensions

Product Net Weight	2 lb 907.029 g
--------------------	-------------------

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	5 piece
Package Level 2 Width	19.3 in 490 mm

Package Level 2 Height	6.7 in 170 mm
Package Level 2 Depth / Length	51.2 in 1300 mm

Additional Information

Brand / Label	Shrink-Kon
Color	Black
Flammability Hazard Rating	Flame Retardant
Number of Batteries	0
Process Temperature Rating	-67 to +230 °F -55 to +110 °C
Product Name	PLASTIC CONDUIT
Product Type	Heat Shrinkable Tubing
Shrink Ratio	3:1
Shrink Temperature	248 °F 120 °C
UPC	786210082752

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	TBM6700
Instructions and Manuals	TBM6700

Classifications

ETIM 6	EC000217 - Shrink tubing
ETIM 7	EC000217 - Shrink tubing
UNSPSC	39121723
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	5073 >> Heat shrinkable tube

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

