

PRODUCT-DETAILS

AF16B-30-01-14

AF16B-30-01-14 250-500V50/60HZ-DC Contactor



General Information

Extended Product Type	AF16B-30-01-14
Product ID	1SBL177061R1401
EAN	3471523122345
Catalog Description	AF16B-30-01-14 250-500V50/60HZ-DC Contactor
Long Description	The AF16B-30-01-14 is a 3 pole - 690 V IEC or 600 UL contactor with 1 built-in auxiliary contact and screw terminals, controlling motors up to 7.5 kW / 400 V AC (AC-3) or 10 hp / 480 V UL and switching power circuits up to 30 A (AC-1) or 30 A UL general use. Thanks to the AF technology, the contactor has a wide control voltage range (250-500 V 50/60 Hz and DC), managing large control voltage variations, reducing panel energy consumptions and ensuring distinct operations in unstable networks. Furthermore, surge protection is built-in, offering a compact solution. AF contactors have a block type design, can be easily extended with add-on auxiliary contact blocks and an additional wide range of accessories.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Instructions and Manuals	1SBC101037M6801
--------------------------	-----------------

Dimensions

Product Net Width	45 mm
Product Net Depth / Length	77 mm
Product Net Height	86 mm
Product Net Weight	0.31 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	1
Standards	IEC/EN 60947-1, IEC/EN 60947-4-1, UL 60947-4-1, CSA C22.2 No. 60947-4-1, IEC 60077-1 (applicable parts), IEC 60077-2 (applicable parts), EN 50155 (applicable parts), TR CU 001/2011, IEC 61373, For compliance confirmation on applicable parts based on your application and combination, please consult your ABB sales representatives.
Rated Operational Voltage	Auxiliary Circuit 690 V Main Circuit 690 V
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I _{th})	acc. to IEC 60947-5-1, q = 40 °C 16 A
Rated Operational Current AC-1 (I _e)	(690 V) 40 °C 30
Rated Operational Current AC-3 (I _e)	(380 / 400 V) 60 °C 18 A
Rated Operational Power AC-3 (P _e)	(380 / 400 V) 7.5 kW
Rated Operational Current AC-15 (I _e)	(500 V) 2 A (690 V) 2 A (24 / 127 V) 6 A (220 / 240 V) 4 A (400 / 440 V) 3 A
Rated Short-time Withstand Current (I _{cw})	for 0.1 s 140 A for 1 s 100 A
Maximum Electrical Switching Frequency	(AC-15) 1200 cycles per hour (DC-13) 900 cycles per hour
Rated Operational Current DC-13 (I _e)	(24 V) 6 A / 144 W (48 V) 2.8 A / 134 W (72 V) 1 A / 72 W (110 V) 0.55 A / 60 W (125 V) 0.55 A / 69 W (220 V) 0.27 A / 60 W (250 V) 0.27 A / 68 W (400 V) 0.15 A / 60 W (500 V) 0.13 A / 65 W (600 V) 0.1 A / 60 W
Rated Control Circuit Voltage (U _c)	50 Hz 250 ... 500 V 60 Hz 250 ... 500 V DC Operation 250 ... 500 V
Operate Time	Between Coil De-energization and NC Contact Closing 13 ... 98 ms Between Coil De-energization and NO Contact Opening 11 ... 95 ms Between Coil Energization and NC Contact Opening 38 ... 90 ms Between Coil Energization and NO Contact Closing 40 ... 95 ms
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 0.75 ... 6 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 4 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Rigid 1/2x 1 ... 6 mm ²
Wire Stripping Length	Main Circuit 10 mm

Degree of Protection	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP40 acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP20
Terminal Type	Screw Terminals

Technical UL/CSA

General Use Rating UL/CSA	(600 V AC) 30 A
Horsepower Rating UL/CSA	(120 V AC) Single Phase 1-1/2 hp (200 ... 208 V AC) Three Phase 5 hp (220 ... 240 V AC) Three Phase 5 hp (240 V AC) Single Phase 3 hp (440 ... 480 V AC) Three Phase 10 hp (550 ... 600 V AC) Three Phase 15 hp

Environmental

Climatic Withstand	Category B according to IEC 60947-1 Annex Q
RoHS Status	Following EU Directive 2011/65/EU

Certificates and Declarations (Document Number)

CB Certificate	CB_SE-96551
CCC Certificate	CCC_2010010304445624
CQC Certificate	CQC2010010304445624
cUL Certificate	UL_20180227_E312527_7_1
Declaration of Conformity - CCC	2020980304001253
Declaration of Conformity - CE	1SBD250002U1000
EAC Certificate	EAC_RU C-FR ME77 B03597
Environmental Information	1SBD250167E1000
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
Instructions and Manuals	1SBC101037M6801
KC Certificate	KC_HW02016-15005C
RoHS Information	1SBD250002U1000
UL Certificate	UL_20140305-E312527_7_1
UL Listing Card	E312527

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	87 mm
Package Level 1 Depth / Length	79 mm
Package Level 1 Height	47 mm
Package Level 1 Gross Weight	0.31 kg
Package Level 1 EAN	3471523122345
Package Level 2 Units	box 27 piece
Package Level 2 Width	250 mm
Package Level 2 Depth / Length	300 mm
Package Level 2 Height	315 mm
Package Level 2 Gross Weight	16.74 kg

Package Level 3 Units

1296 piece

Classifications

Object Classification Code	Q	
ETIM 4	EC000066 - Magnet contactor, AC-switching	
ETIM 5	EC000066 - Magnet contactor, AC-switching	
ETIM 6	EC000066 - Power contactor, AC switching	
ETIM 7	EC000066 - Power contactor, AC switching	
eClass	V11.0 : 27371003	
UNSPSC	39121529	

Categories

Low Voltage Products and Systems → Control Products → Contactors → Block Contactors

