



Main

Range of product	TeSys B
Product or component type	Contacteur
Device short name	LC1BP
Contacteur application	Motor-heating-lighting
Utilisation category	AC-1 AC-3
Control circuit type	AC
Coil type	Standard
Poles description	3P
Pole contact composition	3 NO
[In] rated current	2000 A (<= 40 °C) AC network AC-1 for power circuit 1500 A (<= 55 °C) AC network AC-3 for power circuit
Motor power kW	800 kW at 440 V AC 50/60 Hz 800 kW at 415 V AC 50/60 Hz 750 kW at 660...690 V AC 50/60 Hz 750 kW at 380...400 V AC 50/60 Hz 700 kW at 500 V AC 50/60 Hz 670 kW at 1000 V AC 50/60 Hz 425 kW at 220...230 V AC 50/60 Hz
Auxiliary contact composition	2 NO + 2 NC
[Uc] control circuit voltage	110 V AC 50...400 Hz

Complementary

Control circuit voltage limits	0.85...1.1 U _c operational 50...400 Hz 0.35...0.5 U _c drop-out 50...400 Hz
[Ui] rated insulation voltage	1500 V - for power circuit - conforming to VDE 0110 group C 1000 V - for power circuit - conforming to IEC 60947-4 1000 V - for power circuit - conforming to IEC 60158-1
Mounting mode	Fixed
Mounting support	Bar support bracket Notched mounting rails
Connections - terminals	Power circuit: bars 3 - busbar cross section: 100 x 5 mm
Tightening torque	Power circuit: 35 N.m - on bars
[U _e] rated operational voltage	<= 1000 V AC 50/60 Hz for power circuit
[I _{th}] conventional free air thermal current	2000 A at <= 40 °C for power circuit
I _{rms} rated making capacity	15000 A at 1000 V AC for power circuit conforming to IEC 60947-4 15000 A at 1000 V AC for power circuit conforming to IEC 60158-1
Rated breaking capacity	9000 A at 660...690 V for power circuit conforming to IEC 60947-4 9000 A at 660...690 V for power circuit conforming to IEC 60158-1 5000 A at 1000 V for power circuit conforming to IEC 60947-4 5000 A at 1000 V for power circuit conforming to IEC 60158-1 15000 A at 440 V for power circuit conforming to IEC 60947-4 15000 A at 440 V for power circuit conforming to IEC 60158-1 12000 A at 500 V for power circuit conforming to IEC 60947-4 12000 A at 500 V for power circuit conforming to IEC 60158-1
Associated fuse rating	2000 A gI at <= 440 V for power circuit 1600 A aM at <= 440 V for power circuit
Average impedance	0.13 mOhm at 50 Hz - I _{th} 2000 A for power circuit
Power dissipation per pole	520 W AC-1 - I _{th} 2000 A 290 W AC-3 - I _{th} 2000 A

Inrush power in VA	1300 VA
Hold-in power consumption in VA	31 VA 50/60 Hz
Operating time	50...100 ms opening 100...150 ms closing
Mechanical durability	1200000 cycles
Operating rate	120 cyc/h at <= 55 °C
Height	490 mm
Width	790 mm
Depth	475 mm
Product weight	94 kg

Environment

Standards	BS 5424 IEC 60158-1 IEC 60947-4 NF C 63-110 VDE 0660
Product certifications	BV CSA RINA
Protective treatment	TH TC
Ambient air temperature for operation	-5...55 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without derating in temperature

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Will not be Compliant
REACH	Reference not containing SVHC above the threshold

Contractual warranty

Period	18 months
--------	-----------